

iiyama ProLite XUB3293UHSN-B5 computer monitor 80 cm (31.5") 3840 x 2160 pixels 4K Ultra HD LCD Black

Gamintojas: IIYAMA · Modelis: XUB3293UHSN-B5 · EAN: 4948570121342 · Prekės kodas: 726964



433,91 €

Kaina su PVM

Be PVM: 358,60 €

[Sandėlyje](#)



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ KVM SWITCH
- ✓ USB-C Dock
- ✓ IPS Technology
- ✓ Flicker-free + Blue light
- ✓ Speakers and headphones



Aprašymas

Equipped with the KVM switch, the XUB3293UHSN allows you to connect multiple computers that can be operated over one console (monitor, keyboard, mouse). The USB-C dock provides a clean and practical workspace by using a single cable to both send the signal from your notebook to your monitor and power and charge the notebook from the monitor. Additionally, if your monitor is connected to the Internet with a LAN cable, your notebook will automatically be connected to the network as well. IPS panel guarantees wide viewing angles and natural, highly accurate colours.

Techninė specifikacija

Specifications

Sandėlio grupė

Flat Screens [+271][-238]

Display

Display diagonal	80 cm (31.5")
Display resolution	3840 x 2160 pixels
Native aspect ratio	16:9
Display technology	LCD
Touchscreen	No
HD type	4K Ultra HD
Panel type	IPS
Response time	4 ms
Screen shape	Flat
Contrast ratio (typical)	1000:1
Maximum refresh rate	60 Hz
Display number of colours	1.07 billion colours
Display brightness (typical)	350 cd/m²
Response time measurement type	GTG (Gray to Gray)
Display surface	Matt
Contrast ratio (dynamic)	80000000:1
Viewing angle, horizontal	178°
Viewing angle, vertical	178°
Pixel pitch	0.182 x 0.182 mm
Horizontal scan range	30 - 135 kHz
Viewable size, horizontal	69.8 cm
Viewable size, vertical	39.3 cm
Display diagonal (metric)	80 cm
Colour depth	10 bit
sRGB coverage (typical)	99%
NTSC coverage (typical)	93%

Performance

NVIDIA G-SYNC	No
AMD FreeSync	No
Flicker-free technology	Yes
Low Blue Light technology	Yes

Multimedia

Built-in speaker(s)	Yes
Built-in camera	No

Number of speakers	2
RMS rated power	6 W
Design	
Product colour	Black
Ports & interfaces	
Built-in USB hub	Yes
HDMI	Yes
Headphone out	Yes
USB hub version	3.2 Gen 1 (3.1 Gen 1)
USB upstream port type	USB Type-C
Number of downstream ports	2
Number of USB Type-C upstream ports quantity	1
USB Type-A downstream ports quantity	2
USB Power Delivery (USB PD)	Yes
USB Power Delivery up to	65 W
HDMI ports quantity	1
DisplayPorts quantity	1
Built-in KVM switch	Yes
HDCP	Yes
Network	
Ethernet LAN	Yes
Ergonomics	
VESA mounting	Yes
Cable lock slot	Yes
Height adjustment	Yes
Panel mounting interface	100 x 100 mm
Cable management	Yes
Cable lock slot type	Kensington
Adjustable height (max)	15 cm
Pivot	Yes
Pivot angle	0 - 90°
Swivelling	Yes
Swivel angle range	-45 - 45°
Tilt adjustment	Yes

On Screen Display (OSD)	Yes
On Screen Display (OSD) languages	Czech, German, English, French, Italian, Japanese, Dutch, Polish, Russian
Power	
Energy efficiency class (SDR)	G
Energy efficiency class (HDR)	Not available
Energy consumption (SDR) per 1000 hours	32.9 kWh
Power consumption (typical)	33 W
Power consumption (standby)	0.5 W
Power consumption (off)	0.5 W
AC input voltage	100 - 240 V
AC input frequency	50/60 Hz
Power supply type	Internal
Energy efficiency scale	A to G
Weight & dimensions	
Width (with stand)	714 mm
Depth (with stand)	239.5 mm
Height (with stand)	602 mm
Weight (with stand)	9.9 kg
Height (without stand)	452 mm
Packaging content	
Stand included	Yes
Cables included	AC, USB, HDMI, DisplayPort, USB Type-C
Quick start guide	Yes
Sustainability	
Sustainability certificates	ErP
Other features	
Packaging content	quick start guide, safety guide
Weight	9.9 kg
Width	714 mm
Depth	239.5 mm
Compliance certificates	CE, EAC, PSE, REACH, RoHS, TÜV mark, UKCA, VCCI, WEEE
Ethernet LAN (RJ-45) ports	1

User controls

picture (brightness, contrast, black tuner, sharpness, OD, ACR, ECO, X-res technology), colour (warm, normal, cool, user colour, i-Style colour, blue light reducer), input select, audio (volume, mute), language, OSD settings (OSD H. position, OSD V. position, OSD background, OSD time out, information), setup menu (video mode adjust, HDMI RGB range, KVM, USB-C, USB BC, opening logo, LED, memory recall)

Control panel

Power, Menu, Right / Volume, Left / Eco, Input Select / Exit

Matmenys ir svoris

Matmenys (I × P × A)

79,00cm × 19,00cm × 50,00cm

Svoris

12,12kg