

Sony α ILCE-6400AK 1/1.6" MILC 24.2 MP CMOS 6000 x 4000 pixels Black

Gamintojas: **SONY** · Modelis: **ILCE6400AKB.CEC** · EAN: **4548736166332** · Prekės kodas: **727273**

840,90 €

Kaina su PVM

Be PVM: **694,96 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ MILC 24.2 MP CMOS Touchscreen Black
- ✓ Image sensor size: 1/1.6"
- ✓ Image stabilizer
- ✓ Face tracking
- ✓ ISO sensitivity (min): 100 ISO sensitivity (max): 51200 Fastest camera shutter speed: 1/4000 s Slowest camera shutter speed: 30 s ± 5EV (1/2EV; 1/3EV step)
- ✓ Video recording 3840 x 2160 pixels 4K Ultra HD
- ✓ Built-in microphone Built-in speaker(s) Voice recording Micro-USB HDMI Wi-Fi Near Field Communication (NFC)
- ✓ Lithium-Ion (Li-Ion) 7.3 V

Aprašymas

Grab the best of life.

Despite its compact size and light weight, the α6400 delivers speedy performance and a range of features you'd expect from a full-frame model. Whether you're taking still shots or movies, creative compositions or everyday selfie shots, you'll enjoy beautiful images that you'll want to share, on the go.

Reasons to choose this model

Techninė specifikacija

Specifications

Sandėlio grupė

Digital Cameras [+10][-14]

Picture quality

Camera type	MILC
Megapixel (approx.)	24.2 MP
Sensor type	CMOS
Maximum image resolution	6000 x 4000 pixels
Image sensor size	1/1.6"
Still image resolution(s)	6000 x 4000, 4240 x 2832, 3008 x 2000, 6000 x 3376, 4240 x 2400, 3008 x 1688
Image stabilizer	Yes
Image formats supported	JPEG, Raw
Supported aspect ratios	3:2, 16:9
Total megapixels	25 MP
Image sensor size (W x H)	23.5 x 15.6 mm
Sensor format	Advanced Photo System type-C (APS-C)
Built-in low-pass filter	Yes

Lens system

Focal length range	16 - 50 mm
Minimum aperture number	3.5
Maximum aperture number	5.6
Lens type	Standard zoom
Lens mount interface	Sony E

Focusing

Focus adjustment	Auto/Manual
Auto focusing (AF) modes	Continuous Auto Focus, Single Auto Focus
Auto Focus (AF) object detection	Dog, Eye, Face, People
Face tracking	Yes
Closest focusing distance	0.25 m
Auto Focus (AF) points	425
Auto Focus (AF) points selection	Auto, Manual
Auto Focus (AF) lock	Yes

Exposure

ISO sensitivity (min)	100
ISO sensitivity (max)	51200
Light exposure modes	Aperture priority AE, Auto, Manual
Light exposure correction	± 5EV (1/2EV; 1/3EV step)

Light metering	Centre-weighted
ISO sensitivity	100, 200, 400, 800, 1600, 3200, 6400, 12800, 25600
Light exposure control	Program AE
Auto Exposure (AE) lock	Yes
Shutter	
Fastest camera shutter speed	1/4000 s
Slowest camera shutter speed	30 s
Flash	
Flash modes	Auto, Flash off, Flash on, High-speed synchronization, Red-eye reduction, Slow synchronization
Flash exposure lock	Yes
Flash guide number	6 m
Flash sync-speed	1/160 s
Flash exposure compensation	Yes
Flash exposure correction	±3EV (1/2; 1/3 EV step)
Video	
Video recording	Yes
Maximum video resolution	3840 x 2160 pixels
HD type	4K Ultra HD
Video resolutions	1280 x 720, 1920 x 1080, 3840 x 2160
Motion JPEG frame rate	30 fps
Analog signal format system	NTSC, PAL
Video formats supported	MPEG4, XAVC S
Audio	
Built-in microphone	Yes
Built-in speaker(s)	Yes
Voice recording	Yes
Audio system	stereo
Memory	
Compatible memory cards	MS PRO Duo, MS PRO Duo Mark 2, MS Pro-HG Duo, MicroSD (TransFlash), MicroSDHC, MicroSDXC, SD, SDHC, SDXC
Memory slots	1
Display	
Display	LCD
Touchscreen	Yes

Display diagonal	7.62 cm (3")
Display resolution (numeric)	921600 pixels
Vari-angle LCD display	Yes
Viewfinder	
Viewfinder type	Electronic
Magnification	1.07x
Viewfinder technology	OLED
Ports & interfaces	
HDMI	Yes
USB connector	Micro-USB
HDMI connector type	Micro
Microphone in	Yes
Network	
Wi-Fi	Yes
Near Field Communication (NFC)	Yes
Wi-Fi standards	802.11b, 802.11g, Wi-Fi 4 (802.11n)
Camera	
White balance	Auto, Cloudy, Daylight, Flash, Fluorescent, Fluorescent H, Fluorescent L, Incandescent, Shade
Scene modes	Landscape, Night, Panorama, Portrait, Sports
Shooting modes	Aperture priority, Auto, Manual, Movie, Shutter priority
Photo effects	Black&White, Negative film, Neutral, Sepia, Vivid
Self-timer delay	2,5,10 s
Tripod mounting supported	Yes
Contrast adjustment	Yes
Brightness adjustment	Yes
Camera playback	Single image, Slide show
Subject recognition	Yes
Dioptrre correction	Yes
Dioptr adjustment (D-D)	-4 - 3
Histogram	Yes
Orientation sensor	Yes
Camera file system	DPOF, Exif, Raw
Anti-dust function	Yes
Smartphone/tablet remote support	Yes

High Dynamic Range (HDR) supported	Yes
RAW image processing	Yes
Built-in interval timer	Yes
Metadata supported	Yes
Histogram options	Brightness, RGB
Firmware upgradeable	Yes
Built-in processor	Yes
Image processor	BIONZ X
Design	
Product colour	Black
Battery	
Battery technology	Lithium-Ion (Li-Ion)
Battery voltage	7.3 V
Battery life (CIPA standard)	400 shots
Battery capacity	1020 mAh
Battery type	NP-FW50
Number of batteries supported	1
Power	
USB Type-C charging port	Yes
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Weight & dimensions	
Width	120 mm
Depth	60 mm
Height	66.9 mm
Weight	403 g
Packaging data	
Quantity per pack	1 pc(s)
Packaging content	
AC adapter included	Yes
Hand strap	Yes
Batteries included	Yes
Quick start guide	Yes
Other features	

Power source type

Battery

Matmenys ir svoris

Matmenys (l × P × A)

16,00cm × 12,00cm × 15,00cm

Svoris

1,01kg