

InLine USB Display AOC Cable, USB-C male to HDMI male (DP Alt Mode), 50m

Gamintojas: **INLINE** · Modelis: **64250A** · EAN: **4043718304035** · Prekės kodas: **729478**



165,90 €

Kaina su PVM

Be PVM: **137,11 €**

Sandėlyje




Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 50 m
- ✓ USB Type-C Straight Male
- ✓ HDMI Straight Male
- ✓ 4096 x 2160 pixels
- ✓ USB Type-C DisplayPort Alternate Mode
- ✓ Black
- ✓ 1 pc(s)



Aprašymas

USB 3.2 Type-C male to HDMI 2.0b A male hybrid cable, hybrid active optical cable (AOC) USB 3.2 Gen.2, bandwidth 10Gb/s

USB Type-C: DisplayPort Alternate Mode, DP1.2 support

Supports computer resolutions to 4K@60Hz

Input: USB Type-C male (video source)

Output: HDMI A male (display)

Plug and Play - no drivers needed

Gold plated contacts

Metal connector: Zinc alloy housing - sturdy and robust

AOC Cable: Converts electrical data signals to optical signals

4 cores multimode fiber (high speed data) & 7 cores copper (power and low speed data)

Round cable black PVC jacket, OD: 5.2mm

Supports resolutions up to UHD 3840×2160@60Hz / 4096×2160@60Hz

Supports HDR10, 3D, CEC

Self-detecting function for EDID information

Operation temperature: 0°C-+50°C

Storage temperature: -20°C-+70°C

Techninė specifikacija

Specifications	
Sandėlio grupė	Desktop > Video Cables & Adapters [+2032][-276]
Features	
Cable length	50 m
Connector 1	USB Type-C
Connector 2	HDMI
Connector 1 gender	Male
Connector 2 gender	Male
Connector 1 form factor	Straight
Connector 2 form factor	Straight
HDMI version	2.0b
DisplayPort version	1.2
USB Type-C DisplayPort Alternate Mode	Yes
Maximum resolution	4096 x 2160 pixels
Supported graphics resolutions	4096 x 2160
Refresh rate at maximum resolution	60 Hz
3D	Yes
Product colour	Black
Jacket material	Polyvinyl chloride (PVC)
Connector material	Gold
Plug and Play	Yes
High Dynamic Range (HDR) technology	High Dynamic Range 10 (HDR10)
Operational conditions	
Operating temperature (T-T)	0 - 50 °C
Storage temperature (T-T)	-20 - 70 °C
Weight & dimensions	
Cable diameter	5.2 mm

Weight	1.32 kg
Width	20 mm
Depth	50000 mm
Height	10 mm
Packaging data	
Package width	210 mm
Package depth	215 mm
Package height	80 mm
Package weight	1.5 kg
Package type	Box
Packaging content	
Quantity per pack	1 pc(s)
Other features	
Dimensions (WxDxH)	20 x 50000 x 10 mm