

CyberPower PDU41004 power distribution unit (PDU) 8 AC outlet(s) 1U Black

Gamintojas: **CYBERPOWER** · Modelis: **PDU41004** · EAN: **4712856276701** · Prekės kodas: **731978**



518,90 €

Kaina su PVM

Be PVM: **428,84 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Real-Time Local/Remote Monitoring and Switching
- ✓ User Configurable Color LCD
- ✓ Firmware Upgrade via USB
- ✓ Sequential Outlet ON/OFF Control
- ✓ Digital Real-time Load Display



Aprašymas

CyberPower PDU41004 Switched series power distribution unit provides output from a UPS unit, generator, or utility power to multiple connected devices in datacenter environments. The unit supports remote individual outlet control over the network, allowing administrators to turn on/off connected devices from any location. Administrators can further determine the power sequence used to turn individual outlets on or off.

The power management web interface offers real-time remote monitoring of the PDU vitals of the outlets of networked clients. Event logging via a web browser or network connection allows users to review a history of power conditions. When specified power events occur, automatic event notifications will be sent via email, SMS text, or SNMP trap to designated users so that they can take immediate actions. The featured RJ45 port enables the connection of the optional environmental sensor (ENVIROSENSOR), which can provide real-time temperature and humidity monitoring in an IT center.

The product is also certified to be interoperable and compatible with Cisco Compatible™ network environments, which helps to achieve the best

energy performance possible in the datacenter scenario.

Techninė specifikacija

Specifications	
Sandėlio grupė	Komponenten & Zubehör > AC Adapter/Netzteile [+1981][-847]
Design	
PDU types	Managed, Switched
Rack capacity	1U
Type	Single-phase
Mounting	Horizontal
Housing material	Steel
Product colour	Black
Display	LCD
Ports & interfaces	
AC outlets quantity	8 AC outlet(s)
AC outlet types	C13 coupler
Power plug	C14 coupler
Serial ports quantity	1
Ethernet LAN (RJ-45) ports	4
USB ports quantity	1
Features	
Daisy chain	Yes
LED indicators	Link, Status
Cable length	3.05 m
Security algorithms	802.1x RADIUS, HTTPS, SSH, SSL/TLS
Management features	
Supported network protocols	IPv4/v6, SNMPv1/v3, HTTP/HTTPS, TCP/IP, UDP, DHCP, NTP, DNS, SMTP, SSH, SSL, TLS, Telnet, FTP, Syslog
Firmware upgradeable	Yes
Firmware upgradeable via	USB
Power	
Nominal input voltage	100 - 240 V
Maximum current	12 A
AC input frequency	50 / 60 Hz
Nominal output voltage	100 - 240 V

Certificates

Compliance certificates	RoHS
Certification	FCC Class A, UL60950, UL62368, EN 55032 Class A

Operational conditions

Operating temperature (T-T)	0 - 55 °C
Storage temperature (T-T)	-15 - 60 °C
Operating relative humidity (H-H)	0 - 95%
Storage relative humidity (H-H)	0 - 95%
Operating altitude	0 - 3500 m
Non-operating altitude	0 - 15000 m
Operating temperature (T-T)	32 - 140 °F

Weight & dimensions

Width	433 mm
Depth	112 mm
Height	44 mm
Weight	2.1 kg

Packaging content

Bundled software	PowerPanel Business, PowerPanel Enterprise
Packaging content	PDU41004, User's Manual, Cord Retention Tray, Mounting Brackets, Cable Ties, Screw Kit, Power Cord, Serial Cable

Packaging data

Package weight	3.9 kg
Package width	500 mm
Package depth	250 mm
Package height	65 mm

Sustainability

Sustainability compliance	Yes
---------------------------	-----

Matmenys ir svoris

Matmenys (I × P × A)	25,00cm × 50,00cm × 7,00cm
----------------------	----------------------------