

FSP VITA GD 850W Power supply unit ATX ATX3.1 Black

Gamintojas: **FSP GROUP** · Modelis: **PPA8504702** · EAN: **4711498480361** · Prekės kodas: **732051**



110,90 €

Kaina su PVM

Be PVM: **91,65 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Efficiency $\geq 90\%$ at typical load
- ✓ Quiet and long-lasting 120mm HYB fan
- ✓ Premium, all-black cables for easier cable routing
- ✓ Complete protections: OVP, OCP, OPP, OTP, SCP, UVP, SIP, NLO

Aprašymas

The Future is Now □ ATX 3.1 Ready

Following the latest ATX 3.1 regulation, this series supports 200% power excursion and ensure peak performance with future hardware upgrades.

+5V & 3.3V DC to DC Circuit Design

Increase the efficiency and stabilize the output voltage to ensure system stability.

Powerful Single +12V Rail

Modern CPUs and graphics cards can draw significant amounts of power, especially during peak loads., a single +12V rail PSU offers a good balance of simplicity, power delivery capability, and stability.

Premium, Black Flat Cables

Featuring improved black, flat cables that are soft and easy to bend, users can manage them more easily, saving time and creating more space for optimal cooling performance in your PC build.

105°C Japanese Bulk Capacitor

The bulk capacitor inside serves to support working under an extremely harsh environment, such as with high temperatures, peak voltage fluctuations. It stabilizes the performance for high reliability that your system can count on.

Compact PSU size □ 140 x 150 x 86mm

140mm in length which is relatively shorter than industry standard, it's ideal for compact PC or space-constraint environment without compromising

on performance.

Techninė specifikacija

Specifications	
Sandėlio grupė	Komponenten & Zubehör > AC Adapter/Netzteile [+1981][-847]
Power	
Total power	850 W
AC input voltage	100 - 240 V
AC input frequency	50/60 Hz
Input current	11-5.5 A
Power Factor Correction (PFC) type	Active
Combined power (+3.3V)	100 W
Combined power (+12V)	850 W
Combined power (+5V)	100 W
Combined power (-12V)	3.6 W
Combined power (+5Vsb)	15 W
Max output current (+3.3V)	20 A
Max output current (+12V)	70.83 A
Max output current (+5V)	20 A
Max output current (-12V)	0.3 A
Max output current (+5Vsb)	3 A
Efficiency	90%
Power protection features	Over current, Over power, Over voltage, Overheating, Short circuit, Under voltage
Ports & interfaces	
Motherboard power connector	20+4 pin ATX
Peripheral (Molex) power connectors (4-pin)	4
Motherboard power cable length	60 cm
Number of SATA power connectors	8
SATA power cable length	500 mm
PCI Express power connectors (6+2 pin)	4
CPU power connector (4+4 pin)	Yes
CPU power cable length	70 cm
Cabling type	Non-Modular
Performance	
Purpose	PC

Power supply unit (PSU) form factor	ATX
80 PLUS certification	80 PLUS Gold
ATX version	3.1
EPS version	2.92
Bearing technology	HYB
Design	
Product colour	Black
Cooling type	Active
Fan diameter	12 cm
Number of fans	1 fan(s)
Fan location	Top
Packaging content	
Cables included	CPU, Peripheral (Molex), SATA
Weight & dimensions	
Width	150 mm
Depth	140 mm
Height	86 mm
Matmenys ir svoris	
Matmenys (I × P × A)	14,00cm × 15,00cm × 9,00cm