

ATEN 20M True 4K HDMI 2.0 Active Optical Cable (True 4K@20m)

Gamintojas: **ATEN** · Modelis: **VE781020** · EAN: **4719264649455** · Prekės kodas: **732648**



100,90 €

Kaina su PVM

Be PVM: **83,39 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Supports resolution up to True 4K (4096 x 2160 @ 60Hz 4:4:4)
- ✓ HDMI 2.0 (3D, Deep Color, True 4K); HDCP 2.2 compliant
- ✓ Extends True 4K signals up to 20m
- ✓ Reduced EMI and RFI for lower noise interference
- ✓ High data transfer rate of 18 Gbps
- ✓ Supports multi audio channel - Dolby TrueHD and DTS-HD Master Audio
- ✓ Robust cable pulling strength (Max.10 kg) and compression load resistance (Max.50 kg)
- ✓ Plug-and-play

Aprašymas

ATEN VE781020 True 4K HDMI 2.0 Active Optical Cable utilizes AOC technology that enables conversion between input signals and optical signals for optimum high bandwidth data transmissions. The EMI-resistant optical cables come in 20m with full support of True 4K resolutions. It is fully compliant with HDCP 2.2 standards and meets HDMI 2.0 specifications including 3D, deep color, and data rates up to 18 Gbps. Supported Dolby True HD and DTS-HD Master Audio, the optical cables guarantee lossless audio signal transmissions. The VE781020 optical cable is an ideal solution for extending the reach of your digital signage in a wide range of settings, such as traffic stations, shopping centers, and hospital facilities.

Techninė specifikacija

Specifications

Sandėlio grupė

Desktop > Video Cables & Adapters [+2032][-276]

Features

Cable length

20 m

Connector 1

HDMI Type A (Standard)

Connector 2	HDMI Type A (Standard)
Connector 1 gender	Male
Connector 2 gender	Male
Product colour	Black
Connector contacts plating	Gold
Connector 1 form factor	Straight
Connector 2 form factor	Straight
HDMI version	2
3D	Yes
Supported graphics resolutions	3840 x 2160, 4096 x 2160
Dolby technologies	DTS-HD Master Audio, Dolby TrueHD
Audio Return Channel (ARC)	Yes
HDCP	Yes
HDCP version	2
Data transfer rate	18 Gbit/s
Bandwidth	600 MHz
Maximum refresh rate	60 Hz
Cable jacket material	Polyvinyl chloride (PVC)
Operational conditions	
Operating temperature (T-T)	0 - 50 °C
Storage temperature (T-T)	-20 - 70 °C
Operating relative humidity (H-H)	0 - 85%
Certificates	
Compliance certificates	RoHS
Certification	CE / FCC/ REACH / UL VW-1/ EMC Class-A / Class-B
Weight & dimensions	
Cable diameter	4.5 mm
Weight	650 g
Packaging data	
Quantity per pack	1 pc(s)
Logistics data	
Harmonized System (HS) code	84733080
Matmenys ir svoris	
Matmenys (l × P × A)	10,00cm × 15,00cm × 8,00cm