

ATEN HDMI Extender (T+R) over 1 CAT5e/6 Cable (70m) ,4K / HDBaseT-Lite (Class B)

Gamintojas: **ATEN** · Modelis: **VE801-AT-G** · EAN: **4719264642715** · Prekės kodas: **732651**



243,90 €

Kaina su PVM

Be PVM: **201,57 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Extends HDMI signals over a single Cat 5e/6/6a cable or ATEN 2L-2910 Cat 6 cable
- ✓ HDBaseT Anti-jamming – resists signal interference during high-quality video transmission using HDBaseT technology
- ✓ HDMI (3D, Deep color, 4K); HDCP 2.2 compliant
- ✓ Plug-and-play
- ✓ Superior video quality – up to 4K@35m (Cat 5e/6) / 40m (Cat 6a or ATEN 2L-2910 Cat 6 cable)
- ✓ Rack-mountable



Aprašymas

The VE801 HDMI HDBaseT-Lite Extender extends an HDMI signal up to 70m from the HDBaseT source using one Cat 5e/6/6a cable. It supports HDMI features that include 3D, Deep Color and 4K image resolutions, plus Dolby Digital 5.1, DTS HD audio and it is HDCP compatible. The VE801 all-in-one design provides an easy method for mounting the device in any location. The side panel provides slip-resistant grooves that help prevent accidental drops when installing the unit. The grooves also enhance the ability to see the LED status lights. The VE801 is perfect for digital entertainment centers or any installation that requires superior HDMI video quality to be extended for great distances.

1x VE801T/R HDMI HDBaseT-Lite Extender

2x 0AD6-1F05-26EG Power Adapters

1x User Instructions

Techninė specifikacija

Specifications	
Sandėlio grupė	Desktop > Video Cables & Adapters [+2032][-276]
Features	
Type	AV transmitter & receiver
Maximum resolution	3840 x 2160 pixels
Cable types supported	Cat5, Cat6, Cat6a
Maximum transfer distance	70 m
LED indicators	Yes
Supported video modes	1080p
Bandwidth	340 MHz
HDCP	Yes
Material	Metal
Product colour	Black
Ports & interfaces	
Connectivity technology	Wired
RJ-45 input ports	1
RJ-45 output ports	1
HDMI in	1
Number of HDMI outputs	1
DC-in jack	Yes
Operational conditions	
Operating temperature (T-T)	0 - 50 °C
Storage temperature (T-T)	-20 - 60 °C
Operating relative humidity (H-H)	0 - 80%
Weight & dimensions	
Weight	780 g
Receiver dimensions (WxDxH)	34.3 x 98.6 x 30 mm
Receiver weight	250 g
Transmitter dimensions (WxDxH)	34.3 x 98.6 x 30 mm
Transmitter weight	240 g
Packaging data	
Package width	59 mm
Package depth	239 mm

Package height	160 mm
Package weight	841 g
Packaging content	
AC adapter included	Yes
Technical details	
Compliance certificates	RoHS
Logistics data	
Master (outer) case width	250 mm
Master (outer) case length	325 mm
Master (outer) case height	175 mm
Master (outer) case gross weight	4.6 kg
Master (outer) case net weight	3.9 kg
Products per master (outer) case	5 pc(s)