

ATEN HDMI HDBaseT Small Factor Extender

Gamintojas: **ATEN** · Modelis: **VE811-AT-G** · EAN: **4719264645747** · Prekės kodas: **732654**



370,90 €

Kaina su PVM

Be PVM: **306,53 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ HDBaseT Connectivity – extends an HDMI connection up to 100m via a single Cat 5e/6/6a or ATEN 2L-2910 Cat 6 cable
- ✓ Supports resolutions of up to Ultra HD 4Kx2K and 1080p Full HD
- ✓ Supports HDBaseT Long Reach Mode – up to 150 m via a single Cat 5e/6 cable at resolutions up to 1080p
- ✓ HDCP 2.2 compatible



Aprašymas

The ATEN VE811 HDMI HDBaseT Extender guarantees the optimum HDMI connection up to 100 m over a single Cat 5e/6/6a or ATEN 2L-2910 Cat 6 cable. The VE811 meets HDMI Specification features including 3D, Deep Color, HD lossless audio formats and CEC pass-through. It supports Dolby Digital 5.1, DTS HD audio and video signals at resolutions up to 4K. In addition, the VE811 supports long reach mode, providing an effective means for extending HDMI signals up to 150m over a single Cat 5e/6 cable.

1x VE811T HDMI HDBaseT Transmitter

1x VE811R HDMI HDBaseT Receiver

2x 0AD6-1F05-26EG Power Adapters

1x User Instructions

Techninė specifikacija

Specifications

Sandėlio grupė Desktop > Video Cables & Adapters [+2032][-276]

Features

Type AV transmitter & receiver

Maximum resolution 4096 x 2160 pixels

Cable types supported Cat5e, Cat6, Cat6a

Maximum transfer distance 150 m

Bandwidth 10.2 Gbit/s

Bandwidth 340 MHz

HDCP Yes

Material Metal

Impedance 100 Ω

Product colour Black

Ports & interfaces

Connectivity technology Wired

RJ-45 input ports 1

RJ-45 output ports 1

HDMI in 1

Number of HDMI outputs 1

Audio input 1

Audio output 1

DC-in jack Yes

Power

Operating voltage (transmitter) 5 V

Operating voltage (receiver) 5 V

Operational conditions

Operating temperature (T-T) 0 - 40 °C

Storage temperature (T-T) -20 - 60 °C

Operating relative humidity (H-H) 0 - 80%

Storage relative humidity (H-H) 0 - 80%

Weight & dimensions

Weight 630 g

Receiver dimensions (WxDxH) 86.4 x 73 x 24.7 mm

Receiver weight 170 g

Transmitter dimensions (WxDxH)	86.4 x 73 x 24.7 mm
Transmitter weight	160 g
Packaging data	
Quantity per pack	2 pc(s)
Package width	59 mm
Package depth	239 mm
Package height	160 mm
Package weight	705 g
Packaging content	
Quick start guide	Yes
Logistics data	
Master (outer) case width	250 mm
Master (outer) case length	325 mm
Master (outer) case height	175 mm
Master (outer) case gross weight	4.02 kg
Master (outer) case net weight	3.15 kg
Products per master (outer) case	5 pc(s)