

Vivolink VLHDMIEXT416 AV extender AV transmitter & receiver Black

Gamintojas: **VIVOLINK** · Modelis: **VLHDMIEXT416** · EAN: **5706998558275** · Prekės kodas: **732667**



146,89 €

Kaina su PVM

Be PVM: **121,40 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 4K HDMI Extender set
- ✓ HDMI 1.4(4K@60 4:2:0), HDCP 2.2
- ✓ HDBT extension up to 1080P@70m & 4K@40m
- ✓ Relay control for projection screen
- ✓ Audio de-embedder on Tx
- ✓ CEC pass-through
- ✓ Two way PoC



Aprašymas

HDBaseT extender kit including relay for projector screen Rx unit and audio de-embed on Tx

2 way PoC, IR, RS232, one PSU, HDMI 1.4 and HDCP2.2 compliant

Typical installation:

It can be installed anywhere need to extend AV/IR/RS232 control signals

E.g. Meeting room or Residential or digital signage etc.

Function:

HDMI extender

Relays output on receiver unit can control screen up/down via RS232 codes.

Audio de-embed on transmitter unit for connection to audio system

Point to point Tx to Rx for 70m@1080P,40m 4K

Techninė specifikacija

Specifications	
Sandėlio grupė	Desktop > Video Cables & Adapters [+2032][-276]
Features	
Type	AV transmitter & receiver
Maximum resolution	3840 x 2160 pixels
Cable types supported	Cat5e
Maximum transfer distance	70 m
IR pass-through	Yes
HDCP pass-through	Yes
RS-232 pass-through	Yes
CEC pass-through	Yes
LED indicators	Yes
Supported video modes	3840p
Bandwidth	10.2 Gbit/s
Remote control type	IR + RS232
HDCP	Yes
HDCP & EDID bypass	Yes
Consumer Electronics Control (CEC) support	Yes
Wall mountable	Yes
HDCP version	2.2
Product colour	Black
HDBaseT certified	Yes
Ports & interfaces	
Connectivity technology	Wired
Ethernet LAN	Yes
RJ-45 input ports	1
RJ-45 output ports	1
HDMI in	1
Number of HDMI outputs	1
HDMI version	1.4

RS-232 input ports	1
RS-232 output ports	1
Digital audio optical in	1
Digital audio optical input type	TOSLINK
Video in	1
Video out	1
Serial ports quantity	1
Serial interface type	RS-232
3.5 mm (1/8-inch) in	Yes
3.5 mm (1/8-inch) out	Yes
Remote (IR) input	1
Remote (IR) output	1
DC-in jack	Yes
Power	
AC input voltage	100 - 240 V
AC input frequency	50 - 60 Hz
Operating voltage (transmitter)	12 V
Output current	2 A
Operating voltage (receiver)	12 V
Power consumption (transmitter) (max)	9 W
Power consumption (receiver) (max)	9 W
External power adapter	Yes
Power over Ethernet (PoE)	Yes
Operational conditions	
Operating temperature (T-T)	-25 - 70 °C
Storage temperature (T-T)	-10 - 50 °C
Operating relative humidity (H-H)	0 - 90%
Weight & dimensions	
Width	182 mm
Depth	161 mm
Height	127 mm
Weight	600 g
Packaging data	
Quantity per pack	2 pc(s)

Package width	182 mm
---------------	--------

Package depth	161 mm
---------------	--------

Package height	127 mm
----------------	--------

Package weight	984 g
----------------	-------

Packaging content

AC adapter included	Yes
---------------------	-----

Included power plug types	EU
---------------------------	----

IR blaster included	No
---------------------	----

IR receiver included	No
----------------------	----

Mounting brackets included	Yes
----------------------------	-----

Technical details

Audio support	Yes
---------------	-----