

Vivolink VLHDMIEXTHDB2.0 AV extender AV transmitter & receiver Black

Gamintojas: **VIVOLINK** · Modelis: **VLHDMIEXTHDB2.0** · EAN: **5711783930204** · Prekės kodas: **732668**



475,91 €

Kaina su PVM

Be PVM: **393,31 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Full HDMI 2.0 compliant
- ✓ 18 Gbps bandwidth
- ✓ Slim 4K HDBT extender
- ✓ Two way PoC
- ✓ Support Bi-directional IR and RS232
- ✓ HDCP2.2 compliant



Aprašymas

Transmitter/Receiver HDMI 2.0 18Gbps, Bi-directional IR, RS232 and CEC, one PSU, HDMI 1.4 and HDCP2.2 compliant

Typical installation:

It can be installed anywhere need to extend AV/IR/RS232 control signals
E.g. Meeting room or Residential or digital signage etc.

Function:

HDMI 2.0 extender

Point to point, Tx to Rx for 70m@1080P, 40m 4K@60Hz 4:4:4

Key features:

Full HDMI 2.0 compliant
18 Gbps bandwidth
Slim 4K HDBT extender.
Two way POC
Support Bi-directional IR and RS232
HDCP2.2 compliant

Techninė specifikacija

Specifications	
Sandėlio grupė	Desktop > Video Cables & Adapters [+2032][-276]
Features	
Type	AV transmitter & receiver
Maximum resolution	4096 x 2160 pixels
Cable types supported	Cat5e
Maximum transfer distance	70 m
High Dynamic Range (HDR) supported	Yes
Maximum refresh rate	60 Hz
IR pass-through	Yes
HDCP pass-through	Yes
RS-232 pass-through	Yes
Bidirectional	Yes
CEC pass-through	Yes
LED indicators	Yes
Supported video modes	3840p
Bandwidth	18 Gbit/s
Remote control type	IR + RS232
HDCP	Yes
HDCP & EDID bypass	Yes
Consumer Electronics Control (CEC) support	Yes
Wall mountable	Yes
HDCP version	2.2
Product colour	Black
HDBaseT certified	Yes
Ports & interfaces	
Connectivity technology	Wired
Ethernet LAN	Yes

RJ-45 input ports	1
RJ-45 output ports	1
HDBaseT port	Yes
HDMI in	1
Number of HDMI outputs	1
HDMI version	2
RS-232 input ports	1
RS-232 output ports	1
Video in	1
Video out	1
Serial ports quantity	1
Serial interface type	RS-232
3.5 mm (1/8-inch) in	Yes
3.5 mm (1/8-inch) out	Yes
Remote (IR) input	1
Remote (IR) output	1
DC-in jack	Yes
Power	
Power source type	DC
AC input voltage	100 - 240 V
AC input frequency	50 - 60 Hz
Operating voltage (transmitter)	12 V
Output current	2 A
Operating voltage (receiver)	12 V
Power consumption (transmitter) (max)	14 W
Power consumption (receiver) (max)	14 W
External power adapter	Yes
Power over Ethernet (PoE)	Yes
Operational conditions	
Operating temperature (T-T)	-10 - 50 °C
Storage temperature (T-T)	-10 - 50 °C
Operating relative humidity (H-H)	0 - 90%
Weight & dimensions	
Width	184 mm
Depth	161 mm

Height	126 mm
Weight	500 g
Receiver dimensions (WxDxH)	115 x 84 x 16 mm
Receiver weight	153 g
Transmitter dimensions (WxDxH)	115 x 84 x 16 mm
Transmitter weight	150 g
Packaging data	
Quantity per pack	2 pc(s)
Package width	184 mm
Package depth	161 mm
Package height	126 mm
Package weight	662 g
Packaging content	
AC adapter included	Yes
Included power plug types	EU
Mounting brackets included	Yes
Technical details	
Audio support	Yes