

ATEN 4-Port HDMI Audio/Video Splitter 4Kx2K

Gamintojas: **ATEN** · Modelis: **VS184A** · EAN: **4710423779938** · Prekės kodas: **732678**



91,90 €

Kaina su PVM

Be PVM: **75,95 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Connects one HDMI source to four HDMI displays at the same time
- ✓ HDMI (3D, Deep Color, 4kx2k); HDCP 1.4 Compliant
- ✓ Supports resolutions of up to Ultra HD 4kx2k and 1080p Full HD
- ✓ Supports Dolby True HD and DTS HD Master Audio
- ✓ Long distance transmission – up to 15 m (24 AWG)
- ✓ Supports up to 340MHz bandwidth for high performance video
- ✓ Plug-and-play – no software installation required



Aprašymas

The VS184A HDMI Splitter is the perfect solution for anyone who needs to send one source of digital high definition video to four displays at the same time. It supports all HDMI-enabled equipment, such as DVD players, satellite set-top boxes and all HDMI displays.

The VS184A HDMI Splitter is HDCP (High Bandwidth Digital Content Protection) compliant, making it effective for use with all HDMI displays in home theater applications, as well as in corporate, educational and commercial settings.

Techninė specifikacija

Specifications

Sandėlio grupė

Desktop > Video Cables & Adapters [+2032][-276]

Ports & interfaces

Video ports quantity	5
Video port type	HDMI
Video out	4x HDMI
DC-in jack	Yes

Features

Maximum resolution	4096 x 2160 pixels
Product colour	Black
HD type	4K Ultra HD
3D	Yes
Maximum operating distance	15 m
Maximum refresh rate	60 Hz
Bandwidth	340 MHz
HDCP version	1.4
HDCP	Yes
Plug and Play	Yes
LED indicators	Yes
Dolby technologies	DTS-HD Master Audio, Dolby TrueHD

Power

AC input voltage	5 V
Power consumption (typical)	6.02 W

Weight & dimensions

Width	80 mm
Depth	200 mm
Height	25 mm
Weight	703 g

Packaging data

Quantity per pack	1 pc(s)
Package width	59 mm
Package depth	239 mm
Package height	160 mm
Package weight	825 g

Packaging content

Manual	Yes
--------	-----

Cables included	HDMI
AC adapter included	Yes
Operational conditions	
Operating temperature (T-T)	0 - 50 °C
Storage temperature (T-T)	-20 - 60 °C
Operating relative humidity (H-H)	0 - 80%
Storage relative humidity (H-H)	0 - 80%
Logistics data	
Master (outer) case net weight	14.1 kg
Harmonized System (HS) code	85176990
Master (outer) case width	315 mm
Master (outer) case length	490 mm
Master (outer) case height	338 mm
Master (outer) case gross weight	17.3 kg
Products per master (outer) case	20 pc(s)