

j5create JVA06 Dual HDMI™ Video Capture Card, 1920*1080 Video Capture Resolution, 3 x HDMI ports and 2 x USB ports, Black

Gamintojas: **J5CREATE** · Modelis: **JVA06-N** · EAN: **4712795085563** · Prekės kodas: **733612**



229,90 €

Kaina su PVM

Be PVM: **190,00 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Dual HDMI™ input for capturing 2 channels
- ✓ Full HD video and audio high performance record/playback through USB-C™ 3.1 Gen1
- ✓ Uncompressed 1080p @ 60 FPS capture via HDMI™ 1.3a
- ✓ Supports 1080p 60 HDMI™ loop out (PGM out)
- ✓ Six screen mode configurations with PIP (Picture in Picture) and PBP (Picture by Picture)
- ✓ Easily switch between different screen modes and adjust transition effects with the built-in buttons
- ✓ Directly activate Chroma Key features through the built-in controls
- ✓ Adjustable segmented window arrangements in PBP (Picture by Picture) mode. Flexible audio connection via HDMI™ or add external audio with 3.5 mm mic-in and speaker out audio jack
- ✓ 3 individual audio mixer on/off switches supported. 3 channel volume indicators. Easy DSLR attachment with 2 cold shoe adapters (included). Supports USB-C™ Power Delivery 3.0
- ✓ UVC standard, plug & play. LED activity indicator



Aprašymas

The JVA06 Dual HDMI™ Video Capture allows users to capture uncompressed 1080p video from two HDMI™ sources simultaneously and customize the content in real time. Whether you're live streaming or recording, there are six screen mode configurations available, including PIP (Picture in Picture) and PBP (Picture by Picture) displays. You can quickly adjust the display settings and transitions with the built-in buttons on the device. The

JVA06 also features a Chroma Key application allowing users to drop in a new background image.

With a flexible audio connection via HDMI™ or analog 3.5 mm port, you can record audio directly from your HDMI™ sources and microphone. It has a built-in audio mixer function allowing users to toggle between four different audio settings and three audio inputs (Mic In, HDMI™ A and HDMI™ B).

The JVA06 is perfect for content creators/producers who want to level up their content without spending a fortune and live streamers who want to simplify their setup without compromising the quality of their content. It features a USB-C® host connection with Power Delivery 3.0 and two cold shoe adapters to attach to your DSLR for the perfect combination of ease-of-use and mobility, giving you the ability to live stream without interruptions and charge your connected USB-C device at the same time.

Techninė specifikacija

Specifications	
Sandėlio grupė	Desktop > Video Cables & Adapters [+2032][-276]
Performance	
Product colour	Black
Internal	No
Host interface	USB 3.2 Gen 1 (3.1 Gen 1)
Video capture resolution (max)	1920 x 1080 pixels
LED indicators	USB
Capturing from	Digital camera, Game console, PC
Supported aspect ratios	16:9
Housing material	Aluminium
Cable length	0.6 m
Country of origin	Taiwan
Video	
Analog signal format system	Not supported
Supported resolutions	640 x 480 720 x 480 720 x 576 800 x 600 1280 x 720 1024 x 768 1360 x 768 1280 x 800 1152 x 864 1440 x 900 1280 x 1024 1400 x 1050 1680 x 1050 1600 x 1200 1920 x 1080
Maximum frame rate	60 fps
Supported video modes	1080p
Audio	
Supported audio channels	2
Ports & interfaces	
USB port	Yes
USB connector type	USB Type-A, USB Type-C
USB version	2.0/3.2 Gen 1 (3.1 Gen 1)
USB ports quantity	2

HDMI ports quantity	3
HDMI in	2
Number of HDMI outputs	1
Power	
Power supply type	USB
Output voltage	20 V
Output current	0.9 A
Software	
Windows operating systems supported	Windows 10, Windows 7, Windows 8, Windows 8.1, Yes
Mac compatibility	Yes
Mac operating systems supported	Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina, Mac OS X 10.15.3 Catalina, Mac OS X 11.0 Big Sur, Mac OS X 12.0 Monterey, Yes
Linux operating systems supported	Yes
Bundled software	Recommended software: OBS™
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-10 - 65 °C
Operating relative humidity (H-H)	0 - 80%
Storage relative humidity (H-H)	0 - 85%
Technical details	
Warranty period	2 year(s)
Weight & dimensions	
Width	134.6 mm
Depth	63.7 mm
Height	18.4 mm
Weight	175 g
Packaging data	
Package weight	415 g
Package height	70 mm
Package width	155 mm
Package depth	95 mm
Package type	Box
Packaging content	
Cables included	HDMI, USB Type-C, USB Type-C to USB Type-A

Quick installation guide	Yes
Manual	Yes
Quantity	1
Packaging content	1 x JVA06 Dual HDMI™ Video Capture, 1 x Quick Installation Guide, 1 x USBxC™ 2.0 to USBxC™ cable, 1 x USBxC™ 3.0 to USB™ TypexA cable, 1 x 39.4 in./100 cm HDMI™ cable