

ATEN HDMI & VGA HDBaseT Transmitter with POH (4K@100m) (HDBaseT Class A)

Gamintojas: **ATEN** · Modelis: **VE2812AT** · EAN: **4719264649639** · Prekės kodas: **733634**



439,90 €

Kaina su PVM

Be PVM: 363,55 €

[Sandėlyje](#)



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Extends HDMI or VGA signals over a single Cat 5e/6/6a cable
- ✓ HDMI: 4K / 1080p at distance up to 100m via a Cat 5e/6/6a or ATEN 2L-2910 Cat 6 cable
- ✓ VGA: 1600 x 1200 and 1920 x 1200 up to 100m via a Cat 5e/6/6a or ATEN 2L-2910 Cat 6 cable
- ✓ Supports HDBaseT Long Reach Mode – up to 150 m via a single Cat 5e/6 cable at resolutions up to 1080p
- ✓ Built-in PoH (Power over HDBaseT) function – the VE2812AT receives power supply from the HDBaseT output port on the connected device
- ✓ Supports Auto Switch – allows the VE2812AT automatically switch to a newly plugged-in source



Aprašymas

ATEN VE2812AT is a transmitter for sending VGA (with audio) and HDMI signals up to 100 m over a single Cat 5e/6/6a or ATEN 2L-2910 Cat 6 cable. Featuring built-in PoH (Power over HDBaseT) function, the VE2812AT receives power supply from the HDBaseT output port on the connected device. This eliminates the need for a power adapter and reduces the hassle of power line deployment behind the wall. The VE2812AT guarantees reliable transmission of HDMI signals, supporting 3D, Deep Color, and embedded HD lossless audio formats. It also ensures transmission of VGA (with audio) at distance up to 100 m. In addition, it supports Long Reach Mode up to 150 m via a single Cat 5e/6 cable at resolutions up to 1080p.

1 x VE2812AT Transmitter

1 x RS-232 Terminal Block

4 x Foot Pads
1 x 0AD8-1F05-26M1 Power Adapter
1 x User Instructions

Techninė specifikacija

Specifications	
Sandėlio grupė	Desktop > Video Cables & Adapters [+2032][-276]
Features	
Type	AV transmitter
Maximum resolution	4096 x 2160 pixels
Maximum transfer distance	100 m
Bandwidth	10.2 Gbit/s
Bandwidth	340 MHz
HDCP	Yes
Material	Metal
3D	Yes
Consumer Electronics Control (CEC) support	Yes
HDCP version	2.2
Product colour	Black
Ports & interfaces	
Connectivity technology	Wired
RJ-45 output ports	1
HDBaseT port	Yes
VGA (D-Sub) input ports	1
HDMI in	1
Audio input	1
Remote (IR) output	1
DC-in jack	Yes
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-20 - 60 °C
Operating relative humidity (H-H)	0 - 80%
Weight & dimensions	
Width	123 mm
Depth	143.2 mm

Height	30 mm
Weight	640 g
Packaging data	
Quantity per pack	1 pc(s)
Package width	59 mm
Package depth	239 mm
Package height	160 mm
Package weight	765 g
Logistics data	
Master (outer) case width	250 mm
Master (outer) case length	325 mm
Master (outer) case height	175 mm
Master (outer) case gross weight	4.4 kg
Master (outer) case net weight	3.2 kg
Products per master (outer) case	5 pc(s)