

Vivolink PRO HDMI 5m SLIM CABLE 10.2Gbit

Gamintojas: **VIVOLINK** · Modelis: **PROHDMIS5** · EAN: **5706998893925** · Prekės kodas: **733756**



28,89 €

Kaina su PVM

Be PVM: **23,88 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 5 m
- ✓ HDMI Type A (Standard) Straight Male
- ✓ HDMI Type A (Standard) Straight Male
- ✓ HDMI version: 2.0b
- ✓ 60 Hz 18 Gbit/s
- ✓ DTS-HD Master Audio
- ✓ High Dynamic Range 10 (HDR10)
- ✓ 3D Audio Return Channel (ARC) HDMI Ethernet channel
- ✓ Black

Aprašymas

High Performance and High Speed HDMI 2.0 18Gbit Cable with Ethernet.

Supports Resolutions up to 4K@60Hz 4:4:4 with HDCP 2.2, CEC and ARC

Ultra flexible.

In the market, the HDMI cables is usually thick and hard. If connecting with display, sometimes it is difficulty, even impossible, for small size display because of very limited space. ← ← Secondly, if cable going through complicated condition, flexible HDMI cable is ideal and easy for installation, especially conditions requiring a lot of small radius bending. Hard HDMI cable can't do it.

Techninė specifikacija

Specifications

Sandėlio grupė

Desktop > Video Cables & Adapters [+2032][-276]

Features

Cable length

5 m

Connector 1

HDMI Type A (Standard)

Connector 2	HDMI Type A (Standard)
Connector 1 gender	Male
Connector 2 gender	Male
Product colour	Black
Connector contacts plating	Gold
Connector 1 form factor	Straight
Connector 2 form factor	Straight
HDMI version	2.0b
3D	Yes
Supported graphics resolutions	4096 x 2160
Supported video modes	2160p
Dolby technologies	DTS-HD Master Audio
Audio Return Channel (ARC)	Yes
HDMI Ethernet channel	Yes
HDCP	Yes
HDCP version	2.2
Data transfer rate	18 Gbit/s
High Dynamic Range (HDR) supported	Yes
High Dynamic Range (HDR) technology	High Dynamic Range 10 (HDR10)
Maximum resolution	4096 x 2160 pixels
Maximum refresh rate	60 Hz
AWG wire size	30
Cable material	Copper
Cable jacket material	Polyvinyl chloride (PVC)
Colour depth	16 bit
Plug and Play	Yes
Operational conditions	
Operating temperature (T-T)	-20 - 60 °C
Certificates	
Compliance certificates	RoHS
Weight & dimensions	
Cable diameter	6 mm
Weight	230 g
Packaging data	

Quantity per pack	1 pc(s)
Package width	180 mm
Package depth	168 mm
Package height	63 mm
Package weight	224 g
Logistics data	
Harmonized System (HS) code	84733080