

ATEN UC3310-AT-G video capturing device USB 3.2 Gen 1 (3.1 Gen 1)

Gamintojas: **ATEN** · Modelis: **UC3310** · EAN: **4710469349317** · Prekės kodas: **733809**



435,90 €

Kaina su PVM

Be PVM: **360,25 €**

Sandėlyje




Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Supports two 4K USB camera inputs for seamless switch and an HDMI output
- ✓ Supports USB audio in / out for matrix switching
- ✓ RS-232 connection enables integration with ATEN VK Control System
- ✓ Built-in RS-485 interface to support VISCA protocol for PTZ camera controller connection



Aprašymas

The CAMLIVE MX (UC3310) UVC Camera Seamless Matrix enables the conversion of up to two 4K @ 30 USB camera sources into one HDMI, allowing seamless switch among the sources. Besides, it features the encoding solution supporting 1080p@30 UVC output simultaneously for live broadcasting on popular streaming software such as Microsoft Teams, Zooms, OBS, XSplit, YouTube, Facebook, GoToWebinar, and Twitch, guaranteeing an engaging video conferencing experience with high quality images and sound.

Pushbuttons are built on the front panel for quick and intuitive signal selection. The RS-232 connection enables integration with ATEN VK series and other third-party control systems. The CAMLIVE MX also comes with RS-485 interface to support VISCA protocol for PTZ camera controller connection. An optional rack mount kit is available to give installation flexibility in media cabinets or DIT stations. The CAMLIVE MX delivers plug-and-play convenience with no software drivers needed. In addition, it runs on all major operating systems including windows 10 and macOS 10.1 for all users to customize video streams for various online meeting applications.

Techninė specifikacija

Specifications	
Sandėlio grupė	Desktop > Video Cables & Adapters [+2032][−276]
Performance	
Product colour	Black
Internal	No
Host interface	USB 3.2 Gen 1 (3.1 Gen 1)
Housing material	Metal
Country of origin	Taiwan
Video	
Supported video modes	720p, 1080p, 2160p
Audio	
Audio sampling rate	48 kHz
Audio sampling rate	16 bit
Ports & interfaces	
USB port	Yes
USB connector type	USB Type-A, USB Type-C
USB ports quantity	3
Number of HDMI outputs	1
Power	
Power supply type	DC
Output voltage	12 V
Software	
Windows operating systems supported	Windows 10, Windows 11
Mac compatibility	Yes
System requirements	
Minimum processor	Intel i3 Dual Core 2.8Ghz
Minimum RAM	4000 MB
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-20 - 60 °C
Operating relative humidity (H-H)	0 - 80%
Weight & dimensions	

Width	200 mm
Depth	164.6 mm
Height	44 mm
Weight	980 g
Other features	
Video in	1 x USB3.2 Gen1 Type A, 1 x USB3.2 Gen1 Type C
RS-232 ports	1
Master (outer) case width	370 mm
Master (outer) case height	232 mm
Packaging data	
Package weight	1.65 kg
Package height	117 mm
Package width	207 mm
Package depth	414 mm
Logistics data	
Master (outer) case gross weight	5.5 kg
Master (outer) case length	427 mm
Master (outer) case net weight	3.69 kg
Harmonized System (HS) code	85176200