

Vivolink VLHDMIMAT4X2RS matrix switcher Scaling matrix switcher 7.5 W

Gamintojas: **VIVOLINK** · Modelis: **VLHDMIMAT4X2RS** · EAN: **5706998972637** · Prekės kodas: **733897**



457,90 €

Kaina su PVM

Be PVM: **378,43 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 4x2 HDMI presentation switcher with matrix outputs
- ✓ HDMI 2.0b, 4K@60Hz 4:4:4 8bit, HDR 10, HDCP 2.2
- ✓ RS232, IR and WEB GUI control (not telnet)
- ✓ 4K to 1080p down-scaling
- ✓ SPDIF and 3.5mm output for dual HDMI OUT audio extraction and dual HDMI OUT ARC
- ✓ Smart EDID management
- ✓ True 4K matrix switcher that can be controlled via WEB GUI



Aprašymas

VLHDMIMAT4X2RS is a 4K HDR capable 4x2 HDMI Matrix Switcher that features 18Gbps bandwidth and HDCP2.2 on all inputs and outputs. It's fully compliant with HDMI2.0 standard and backward compatible with old HDMI1.4 sources and displays. SPDIF and 3.5mm audio breakout audio from corresponding HDMI outputs.

Smart EDID management.

True 4K matrix switcher that can be controlled via WEB GUI (not telnet)

Techninė specifikacija

Specifications	
Sandėlio grupė	Desktop > Video Cables & Adapters [+2032][-276]
Features	
Product type	Scaling matrix switcher
Maximum resolution	3840 x 2160 pixels
Bandwidth	18 Gbit/s
HDCP	Yes
HDCP version	2.2
High Dynamic Range (HDR) supported	Yes
Extended display identification data (EDID)	Yes
Audio formats supported	PCM
Design	
Housing colour	Black
Control type	Buttons
LED indicators	Yes
Remote control included	Yes
Display	
Built-in display	No
Ports & interfaces	
HDMI input ports quantity	4
HDMI output ports quantity	2
HDMI version	2.0b
RJ-45 input ports	1
Digital audio optical out	1
USB connector type	Micro-USB
USB ports quantity	1
Ethernet LAN (RJ-45) ports	1
RS-232 ports	1
Audio (L/R) out	1
Power	
Power consumption (max)	7.5 W
AC input voltage	100 - 240 V
AC input frequency	50 - 60 Hz

Output current	1000 mA
----------------	---------

Output voltage	12 V
----------------	------

Operational conditions

Operating temperature (T-T)	-5 - 55 °C
-----------------------------	------------

Logistics data

Harmonized System (HS) code	85299097
-----------------------------	----------

Weight & dimensions

Width	200 mm
-------	--------

Depth	100 mm
-------	--------

Height	28.5 mm
--------	---------

Weight	860 g
--------	-------

Package width	264 mm
---------------	--------

Package depth	233 mm
---------------	--------

Package height	84 mm
----------------	-------

Package weight	1.05 kg
----------------	---------

Packaging content

Cables included	IR sensor
-----------------	-----------

Mounting brackets included	No
----------------------------	----

AC adapter included	Yes
---------------------	-----