Zyxel GS1350-6HP-EU0101F network switch Managed L2 Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) Grey

Gamintojas: **ZYXEL** · Modelis: **GS1350-6HP-EU0101F** · EAN: **4718937604500** · Prekės kodas: **734397**

162,90 €

Kaina su PVM

Be PVM: **134,63 €**

Sandėlyje

Prekė internetu
Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Auto camera recovery
- ✓ Large power budget
- ✓ Up to 250 meters transmission
- ✓ Intuitive PoE usage LED
- ✓ Enhanced surge & ESD protection

Aprašymas

Just For Surveillance
Crafted for CCTV, Zyxel introduces the brand-new GS1350 smart managed switch for surveillance applications

New outlook
Coated in titanium grey, the GS1350 excels with an eye-catching identity dedicated for surveillance Switch.

Specialized PoE software features for surveillance

Detect and recover failed IP cameras and powered devices automatically with customizable granular parameters suitable for any types of devices and scenarios.
Delivers nonstop power to keep cameras in operation, even if switch under-goes maintenance for firmware or configuration updates, significantly

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

reducing reboot time.

Easy for long-distance deployment
Traditionally, PoE switch delivers power and data within the distance of the 100 meter limitation. The GS1350 series fulfills the need to deploy IP camera or power devices using existing Cat 5e cable to distant locations. By enabling extended-range mode, instantly achieve distant deployments up to 250m. Save your money and effort with simply one PoE.

High power budget, intuitive front panel design
The GS1350 series includes four models with large power budgets of up to 375 W accommodating the requirement for powering up multiple IP cameras. The intuitive LED indicator on the front panel allows inspecting real-time PoE status. In addition, the one-touch “Restore” button on GS1350 Series helps effortless recovery from misconfigurations.

Unique hardware, robust design

Stabilized power
Filters electrical noise and surge to ensure supplying stable power to PoE and the system.

Selected power supply
2X Surge and ESD protection.

Isolated Circuit Design
Provides protection to isolate power surges from Ethernet and power supply.

Intelligent System Monitor
Keeps the system operational from anomalies.

Patented Ethernet Protection
- 4X Surge protection.
- 2X ESD resistant.

Techninė specifikacija

Specifications	
Sandėlio grupė	> Netzwerk > Switches [+1607][-273]
Management features	
Switch type	Managed
Switch layer	L2
Web-based management	Yes
Configuring Location Settings (CLI)	Yes
System event log	Yes
MIB support	RFC 1066, RFC 1213, 1157, RFC 1493, RFC 1643, RFC 1757, RFC 2011, 2012, 2013, RFC 2233, RFC 2358, RFC 2674, RFC 2819, 2925, RFC 3621, RFC 4293, RFC 4292, RFC 4022, RFC 4113
Ports & interfaces	
Basic switching RJ-45 Ethernet ports quantity	5

Basic switching RJ-45 Ethernet ports type	Gigabit Ethernet (10/100/1000)
Installed SFP modules quantity	0
Installed SFP+ modules quantity	0
SFP module slots quantity	1
Network	
Networking standards	IEEE 802.1D, IEEE 802.1Q, IEEE 802.1ab, IEEE 802.1p, IEEE 802.1w, IEEE 802.3, IEEE 802.3ab, IEEE 802.3ad, IEEE 802.3af, IEEE 802.3at, IEEE 802.3az, IEEE 802.3bt, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z
10G support	No
Copper ethernet cabling technology	10BASE-T, 100BASE-TX, 1000BASE-T
Port mirroring	Yes
Flow control support	Yes
Broadcast storm control	Yes
Rate limiting	Yes
Spanning tree protocol	Yes
VLAN support	Yes
Virtual LAN features	MAC address-based VLAN, Port-based VLAN
Number of VLANs	256
Optical fiber	
Fiber ethernet cabling technology	1000BASE-X
Data transmission	
MAC address table	8000 entries
Switching capacity	12 Gbit/s
Forwarding rate	8.9 Mpps
Packet buffer memory	0.525 MB
Security	
DHCP features	DHCP client, DHCP relay, DHCP snooping
IGMP snooping	Yes
IGMP proxy	Yes
Security algorithms	SNMP, SNMPv3, SSH, SSL/TLS
MAC address filtering	Yes
Loop protection	Yes
Queue scheduling algorithms	SPQ, WFQ, Weighted Round Robin (WRR)
Multicast features	
Multicast support	Yes

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

Design	
Product colour	Grey
LED indicators	Yes
Wall mountable	Yes
Performance	
Firmware upgradeable	Yes
Mean time between failures (MTBF)	2021885.87 h
Power	
Power supply included	Yes
DC input voltage	52 - 57 V
Power consumption (max)	72 W
Power over Ethernet (PoE)	
Power over Ethernet (PoE)	Yes
Power over Ethernet (PoE) ports quantity	5
Total Power over Ethernet (PoE) budget	60 W
Operational conditions	
Operating temperature (T-T)	-20 - 50 °C
Storage temperature (T-T)	-40 - 70 °C
Operating relative humidity (H-H)	5 - 95%
Storage relative humidity (H-H)	5 - 95%
Heat dissipation	245.52 BTU/h
Weight & dimensions	
Width	193 mm
Depth	84 mm
Height	26 mm
Weight	410 g
Logistics data	
Harmonized System (HS) code	85176990
Matmenys ir svoris	
Svoris	1,16kg

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903