

ACT Gigabit Ethernet Media Converter

Gamintojas: **ACT** · Modelis: **AC4451** · EAN: **8716065517897** · Prekės kodas: **734617**



44,90 €

Kaina su PVM

Be PVM: **37,11 €**

Sandėlyje



Prekė internetu

Nuskuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Gigabit Media Converter for converting Gigabit Ethernet over fiber to Gigabit Ethernet over copper (RJ45)
- ✓ Converts Gigabit Ethernet over copper (RJ45) to Gigabit Ethernet over fiber
- ✓ Suited for one singlemode or multimode Uncoded SFP transceiver
- ✓ Link Fault Passthrough (LFP) support
- ✓ Auto-negotiation support
- ✓ Compact metal housing



Aprašymas

The AC4451 Gigabit Ethernet Media Converter provides a flexible high-performance solution for a fast and easy transition from Gigabit Ethernet over fiber to Gigabit Ethernet over copper (RJ45) and vice versa. The unmanaged media converter has an open SFP slot for accommodating one singlemode or multimode uncoded SFP transceiver. Additionally, the Ethernet media converter features Link Fault Passthrough (LFP) for detecting link failures. Different work modes can be set by the on-board dip switches.

Techninė specifikacija

Specifications

Sandėlio grupė

> Netzwerk > Switches [+1607][(-273)]

Network

Maximum data transfer rate	1000 Mbit/s
Converter input interface	10Base-T, 100BASE-FX, 1000Base-LX, 1000Base-SX, 1000Base-T
Networking standards	IEEE 802.3, IEEE 802.3ab, IEEE 802.3u, IEEE 802.3z
Ethernet interface type	Gigabit Ethernet
Ethernet LAN data rates	10,100,1000 Mbit/s
Auto-negotiation	Yes
Link Fault Pass-through (LFP)	Yes

Performance

Fiber mode structure	Multi-mode, Single-mode
----------------------	-------------------------

Features

Internal	No
LED indicators	Activity, FDX, Link, Power, Speed
Product colour	Black
Housing material	Metal

Ports & interfaces

Fiber optic connector	SFP
Connectivity technology	Wired
Ethernet LAN (RJ-45) ports	1
DC-in jack	Yes

Power

Output voltage	5 V
Output current	1 A

Weight & dimensions

Width	70 mm
Depth	97 mm
Height	26 mm
Weight	171 g

Operational conditions

Operating temperature (T-T)	0 - 60 °C
Storage temperature (T-T)	-20 - 70 °C

Packaging content

AC adapter included	Yes
---------------------	-----

Packaging data

Package type

Box

Matmenys ir svoris

Svoris

1,00kg