

InLine 17202W DisplayPort cable 2 m White

Gamintojas: **INLINE** · Modelis: **17202W** · EAN: **4043718347476** · Prekės kodas: **734853**



19,90 €

Kaina su PVM

Be PVM: **16,45 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 2 m
- ✓ DisplayPort Straight Male
- ✓ DisplayPort Straight Male
- ✓ DisplayPort version: 1.4
- ✓ 7680 x 4320 pixels 120 Hz 32.4 Gbit/s
- ✓ White



Aprašymas

High resolution support for modern workplaces: Transmits razor-sharp images with up to 7680x4320 pixels at 60Hz – ideal for CAD, video editing, or presentation technology.

Reliable signal quality thanks to triple shielding: The robust cable construction effectively protects against electromagnetic interference – for a stable and secure connection.

Long-term investment security: With DisplayPort 1.4 specification, HDR support, and 8K compatibility, the cable meets the highest technical standards.

Professional workmanship with gold-plated contacts: Reduces contact resistance and extends service life with frequent reconnection – particularly important in changing system environments.

Universally applicable in IT and digital signage: Reliably connects PCs, workstations, monitors, and large displays in professional applications.

The InLine® DisplayPort 1.4 cable series offers a professional connection solution for demanding AV installations in office, technical, and industrial environments. It supports the transmission of image content in Ultra High Definition with a resolution of up to 7680x4320 (8K@60Hz) as well as 4K

content with high refresh rates of up to 120Hz. Thanks to support for HDR, RGB/4:4:4, 4:2:2, and 12-bit color depths, the cable delivers excellent image quality and high compatibility.

The triple-shielded design effectively protects against external interference and enables reliable data transmission—ideal for multi-monitor setups, digital signage solutions, or control rooms. Gold-plated contacts ensure durable, stable connections—even with frequent changes of connected devices. The series is ideal for a wide range of installation scenarios, both stationary and mobile.

DisplayPort connector to DisplayPort connector

DisplayPort version: 1.4

Supported resolutions: FUHD 7680x4320 8K@60Hz, UHD 3840x2160 120HZ RGB/4:4:4 8bit HDR OFF, UHD 3840x2160 120HZ RGB/4:2:2 12bit HDR ON, UHD 3840x2160 60HZ RGB/4:4:4 12bit HDR ON, FullHD 1920x1080

Shielding: triple shielded

Color: white

Contacts: gold-plated

Packaging: PE bag with EAN code

Techninė specifikacija

Specifications	
Sandėlio grupė	> Kabel und Adapter > Displayport Kabel und Adapter [+1987][-131]
Features	
Cable length	2 m
Connector 1	DisplayPort
Connector 2	DisplayPort
Connector 1 gender	Male
Connector 2 gender	Male
Maximum resolution	7680 x 4320 pixels
Product colour	White
Connector 1 form factor	Straight
Connector 2 form factor	Straight
Connector contacts plating	Gold
DisplayPort version	1.4
Supported graphics resolutions	1920 x 1080 (HD 1080), 3840 x 2160, 7680 x 4320
Maximum refresh rate	120 Hz
Magnetically shielded	Yes
Number of shielding layers	3
AWG wire size	28
High Dynamic Range (HDR) supported	Yes
Data transfer rate	32.4 Gbit/s
Colour sampling	4:2:2, 4:4:4
Cable type	Round cable

Certificates

Compliance certificates	RoHS, TÜV mark, UL
-------------------------	--------------------

Weight & dimensions

Cable diameter	7 mm
----------------	------

Weight	133 g
--------	-------

Packaging data

Package width	150 mm
---------------	--------

Package depth	230 mm
---------------	--------

Package height	30 mm
----------------	-------

Package weight	140 g
----------------	-------

Package type	Polybag
--------------	---------

Packaging content

Quantity per pack	1 pc(s)
-------------------	---------

Logistics data

Country of origin	Taiwan
-------------------	--------

Other features

Depth	2000 mm
-------	---------

Height	13 mm
--------	-------

Length	2000 mm
--------	---------

Width	20 mm
-------	-------

Matmenys ir svoris

Svoris	0,14kg
--------	--------