

LevelOne GEP-2861 network switch Managed L2 Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) 1U Black

Gamintojas: **LEVELONE** · Modelis: **GEP-2861** · EAN: **4015867227848** · Prekės kodas: **735404**



651,90 €

Kaina su PVM

Be PVM: **538,76 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 24 Gigabit PoE+ ports and 4 Gigabit SFP ports
- ✓ Total PoE power budget: 390W, up to 30W per port
- ✓ IEEE 802.3af/at PoE compliant to simplify deployment and installation
- ✓ Supports working temperature -10°C~50°C
- ✓ 6KV surge protection, 6KV contact / 8KV air ESD protection



Aprašymas

The levelone GEP-2861 is a 28-Port L2 Managed Gigabit PoE Switch that supports up to 24*10/100/1000M PoE ports and 4*1000M SFP ports. 24*10/100/1000M ports support PoE+ and total up to 390W PoE power budget, conforming to IEEE 802.3af/at standard, single port PoE power up to 30W. supports L2 management, such as QoS, VLAN, MSTP, Multi-broadcast, ports management and PoE management. It has a high anti-interference ability, the product supports 6KV surge protection, and 6KV contact / 8KV air ESD protection. supports 19" rack mount and desktop installation, reliable and durable, and can be used in security network video monitoring, network engineering and other occasions. GEP-2861 provides high HW performance and environment flexibility for SMBs and Enterprises. GEP-2861 is ideal to deliver management simplicity, optimum user experience, and lower total cost of ownership.

Techninė specifikacija

Specifications	
Sandėlio grupė	> Netzwerk > Switches [+1607][-273]
Management features	
Switch type	Managed
Switch layer	L2
Quality of Service (QoS) support	Yes
Ports & interfaces	
Basic switching RJ-45 Ethernet ports quantity	24
Basic switching RJ-45 Ethernet ports type	Gigabit Ethernet (10/100/1000)
Installed SFP modules quantity	0
Installed SFP+ modules quantity	0
Gigabit Ethernet (copper) ports quantity	24
SFP module slots quantity	4
Console port	RJ-45
Power connector	AC-in jack
Network	
Networking standards	IEEE 802.1D, IEEE 802.1Q, IEEE 802.1p, IEEE 802.1s, IEEE 802.3, IEEE 802.3ab, IEEE 802.3ad, IEEE 802.3af, IEEE 802.3at, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z
10G support	No
Copper ethernet cabling technology	10BASE-T, 1000BASE-T, 100BASE-TX
Port mirroring	Yes
Broadcast storm control	Yes
Ethernet LAN data rates	10,100,1000 Mbit/s
VLAN support	Yes
Data transmission	
MAC address table	16000 entries
Switching capacity	56 Gbit/s
Jumbo frames support	Yes
Jumbo frames	10000
Packet buffer memory	4 MB
Security	
Access Control List (ACL)	Yes
BPDU filtering/protection	Yes

Password protection	Yes
Multicast features	
Multicast support	Yes
Design	
Rack mounting	Yes
Stackable	No
Form factor	1U
Product colour	Black
LED indicators	Activity, Link, PoE, Speed, System
Performance	
Firmware upgradeable	Yes
Fanless	No
Power	
Power source	AC
Power supply included	Yes
AC input voltage	100 - 240 V
AC input frequency	50 - 60 Hz
Power over Ethernet (PoE)	
Power over Ethernet (PoE)	Yes
Power over Ethernet (PoE) power per port	30 W
Total Power over Ethernet (PoE) budget	390 W
Operational conditions	
Operating temperature (T-T)	-10 - 50 °C
Storage temperature (T-T)	-40 - 85 °C
Operating relative humidity (H-H)	0 - 95%
Storage relative humidity (H-H)	0 - 95%
Weight & dimensions	
Width	442 mm
Depth	285 mm
Height	44 mm
Weight	4 kg
Packaging content	
Cables included	AC
Quick start guide	Yes

Rack mount kit	Yes
----------------	-----

Packaging data

Package type	Box
Package width	395 mm
Package depth	90 mm
Package height	530 mm
Package weight	4.8 kg

Certificates

Certification	CE, RoHS
---------------	----------

Logistics data

Country of origin	China
Harmonized System (HS) code	85176990

Matmenys ir svoris

Svoris	4,57kg
--------	--------