

LevelOne IGP-1061 network switch Managed L2 Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) Black

Gamintojas: **LEVELONE** · Modelis: **IGP-1061** · EAN: **4015867227886** · Prekės kodas: **735405**



454,90 €

Kaina su PVM

Be PVM: **375,95 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 8 Gigabit PoE ports and 2 Gigabit SFP ports
- ✓ Port 1~2 10/100/1000Base-T RJ45(IEEE 802.3bt) PoE 90W
- ✓ Port 3~8 support IEEE 802.3at Power over Ethernet Plus (PoE+)
- ✓ Compatible with IEEE802.3af/at/bt
- ✓ Support L2 management, such as QoS, VLAN, MSTP, Multi-broadcast, ports management and PoE management
- ✓ Supports ERPS for ring topology
- ✓ 6KV surge protection, 8KV contact /15KV air ESD protection
- ✓ Provides DIN-rail, wall or desktop mounting
- ✓ 40°C to 75°C operating temperature range



Aprašymas

The LevelOne IGP-1061 L2 Managed Gigabit PoE Industrial Switch, provides 8 PoE ports 10/100/1000Base plus 2 port Gigabit SFP to enable high speed network at mission-critical environment. With the industrial standard DIN-rail mount, plus the clearly visible status LEDs provide simple monitoring of port link activity. Moreover, the SFP slots support pluggable modules that enabling you to choose from a variety of transceivers. This switch is Power Sourcing Equipment (PSE), and it is fully complied with IEEE802.3af/at/bt PoE standard at maximum 90W(1-2 port) power budget. It helps to save infrastructure wiring costs dramatically by eliminating electric wiring and less UPS needed.

Techninė specifikacija

Specifications	
Sandėlio grupė	> Netzwerk > Switches [+1607][-273]
Management features	
Switch type	Managed
Switch layer	L2
Quality of Service (QoS) support	Yes
Web-based management	Yes
ARP inspection	Yes
Ports & interfaces	
Basic switching RJ-45 Ethernet ports quantity	8
Basic switching RJ-45 Ethernet ports type	Gigabit Ethernet (10/100/1000)
Installed SFP modules quantity	2
Installed SFP+ modules quantity	0
Gigabit Ethernet (copper) ports quantity	8
Console port	RJ-45
Network	
Networking standards	IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3bt, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z
10G support	No
Copper ethernet cabling technology	10BASE-T, 100BASE-TX, 1000BASE-T
Port mirroring	Yes
Flow control support	Yes
Link aggregation	Yes
Broadcast storm control	Yes
Spanning tree protocol	Yes
Auto-negotiation	Yes
VLAN support	Yes
Virtual LAN features	MAC address-based VLAN, Port-based VLAN, Private VLAN, Protocol-based VLAN, Tagged VLAN, Voice VLAN
Data transmission	
MAC address table	8000 entries
Static route	Yes
Jumbo frames support	Yes
Jumbo frames	10000

Security

DHCP features	DHCP Option 82, DHCP client, DHCP relay, DHCP snooping
MAC address filtering	Yes
BPDU filtering/protection	Yes
Password protection	Yes

Multicast features

Multicast support	Yes
-------------------	-----

Design

Rack mounting	No
Product colour	Black
LED indicators	Activity, Link, PoE, Power
DIN rail mounting	Yes

Performance

Internal memory	1024 MB
Flash memory	128 MB
Noise level	0 dB
Fanless	Yes
Mean time between failures (MTBF)	338634 h

Power

Power source	DC
DC input voltage	48 - 57 V
Power consumption (typical)	5 W
Power consumption (max)	380 W

Power over Ethernet (PoE)

Power over Ethernet (PoE)	Yes
Power over Ethernet (PoE) power per port	10 W
Total Power over Ethernet (PoE) budget	360 W

Operational conditions

Operating temperature (T-T)	-40 - 75 °C
Storage temperature (T-T)	-40 - 85 °C
Operating relative humidity (H-H)	0 - 95%
Storage relative humidity (H-H)	0 - 95%

Weight & dimensions

Width	165 mm
-------	--------

Depth	115 mm
Height	50 mm
Weight	500 g
Packaging content	
Quick start guide	Yes
Packaging data	
Package type	Box
Package width	270 mm
Package depth	181 mm
Package height	74 mm
Package weight	1.13 kg
Certificates	
Certification	CE, RoHS
Logistics data	
Country of origin	China
Harmonized System (HS) code	85176990
Matmenys ir svoris	
Svoris	1,18kg