

Lindy 10m USB 3.2 Gen 2 & DP 1.4 Type C Hybrid Cable

Gamintojas: LINDY · Modelis: 43398 · EAN: 4002888433983 · Prekės kodas: 735553



286,90 €

Kaina su PVM

Be PVM: 237,11 €

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 8m USB 3.2 Gen 1 & DP 1.4 Type C Hybrid Cable for data and video extension
- ✓ Data transfer rates up to 5Gbps
- ✓ Supports DisplayPort Alternate Mode and DP 1.4 (2 lanes) with video resolutions up to 4K 3840x2160@30Hz
- ✓ Supports Power Delivery up to 60W (20V 3A)



Aprašymas

The Lindy USB 3.2 Gen 1 & DP 1.4 Type C Hybrid Cable is a unique solution, which uses optical fiber as high-speed transmission medium to perfectly transmit USB 3.2 as well as DP 1.4 data over a distance of 8m. It combines data, video and USB Power Delivery into a single, high performance cable which makes it a great solution for use in modern meeting rooms and classrooms when connecting LFDs and touchpanels. A more flexible construction makes this cable simple to install, with increased resistance to RFI/EMI ensures that the cable can be installed in sensitive environments.

The cable also supports Power Delivery up to 60W (20V / 3A). Compatible with USB 3.2 Type C and Thunderbolt 3/4 equipped computers, this is a perfect extension tool for the latest laptops, Macbooks and Type C computers. With plug and play functionality, this extension cable can be installed quickly and with minimum fuss,

Techninė specifikacija

Specifications

Sandėlio grupė > Kabel und Adapter > Displayport Kabel und Adapter [+1987][-131]

Features

USB version	USB 3.2 Gen 1 (3.1 Gen 1)
Connector 1	USB C
Connector 2	USB C
Connector 1 gender	Male
Connector 2 gender	Male
Product colour	Black
Connector 1 form factor	Straight
Connector 2 form factor	Straight
AWG wire size	21
Cable jacket material	Polyvinyl chloride (PVC)
Connector shielding	Yes
Connector shield material	Copper
Connector housing material	Plastic
Maximum data transfer rate	5000 Mbit/s
Maximum data transfer rate	5 Gbit/s
USB Power Delivery (USB PD)	Yes
USB Power Delivery up to	60 W
USB Type-C DisplayPort Alternate Mode	Yes
DisplayPort version	1.4
Maximum resolution	3840 x 2160 pixels
Nominal attenuation	<10dB/km@850nm,<8dB/km@1300nm

Power

Output voltage	20 V
Output current (max)	3 A

Weight & dimensions

Cable length	10 m
Cable diameter	6.5 mm
Weight	610 g
Bend radius (min)	10 cm

Packaging data

Package type	Box
--------------	-----

Package width	240 mm
Package depth	240 mm
Package height	65 mm
Package weight	770 g
Packaging content	
Quantity per pack	1 pc(s)
Manual	Yes
Operational conditions	
Operating temperature (T-T)	-10 - 70 °C
Storage temperature (T-T)	-40 - 85 °C
Certificates	
Compliance certificates	CE, Federal Communications Commission (FCC), REACH, RoHS, UKCA
Sustainability	
Sustainability compliance	Yes
Matmenys ir svoris	
Svoris	0,95kg