

InLine 15322 DisplayPort cable 2.5 m Black

Gamintojas: **INLINE** · Modelis: **15322** · EAN: **4043718336418** · Prekės kodas: **735577**



16,90 €

Kaina su PVM

Be PVM: **13,97 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 2.5 m
- ✓ DisplayPort Straight Male
- ✓ DisplayPort Straight Male
- ✓ DisplayPort version: 1.4
- ✓ 7680 x 4320 pixels 120 Hz 32.4 Gbit/s
- ✓ Black

Aprašymas

High transmission quality up to 8K: Supports resolutions up to 7680×4320 at 60 Hz – ideal for demanding AV applications.

Future-proof specification: Compatible with DisplayPort 1.4 including HDR, DSC 1.2 and MST for modern multi-monitor setups.

Reliable signal stability: Thanks to high-quality workmanship with gold-plated contacts and robust sheathing.

Backward compatible for maximum flexibility: Also supports older DP versions for versatile use.

Ideal for professional environments: Perfect for conference rooms, control centres, digital workplaces and system integration.

The InLine® DisplayPort 1.4 cable is the reliable solution for professional image and video transmission. It enables a bandwidth of up to 32.4 Gb/s and thus supports resolutions of up to 8K at 60 Hz and 4K at 120 Hz. This makes it ideal for demanding AV applications in companies, educational institutions or control centres.

Gold-plated contacts ensure optimum conductivity and reliable protection against corrosion, even with frequent use. The solid workmanship ensures high durability, even with intensive use. Thanks to Display Stream Compression (DSC) 1.2, High Dynamic Range (HDR) and Multi-Stream Transport (MST), the cable is ideally designed for modern systems. Backward compatibility with older DisplayPort versions allows seamless integration into existing infrastructures.

System houses, IT service providers and installers benefit from the easy handling and high operational reliability. The InLine® DisplayPort 1.4 cable is therefore the ideal choice for professional applications in digital signage, conference rooms or for multi-monitor setups in modern working environments.

Standard: DisplayPort 1.4

Max. resolution: 8K@60 Hz / 4K@120 Hz

Bandwidth: 32.4 Gb/s

Features: HDR, DSC 1.2, MST

Backward compatible with: DP 1.3 / 1.2 / 1.1

Contact material: Gold-plated

Colour: Black

Connector: DisplayPort (male to male)

Techninė specifikacija

Specifications	
Sandėlio grupė	> Kabel und Adapter > Displayport Kabel und Adapter [+1987][-131]
Features	
Cable length	2.5 m
Connector 1	DisplayPort
Connector 2	DisplayPort
Connector 1 gender	Male
Connector 2 gender	Male
Maximum resolution	7680 x 4320 pixels
Product colour	Black
Connector 1 form factor	Straight
Connector 2 form factor	Straight
Connector contacts plating	Gold
DisplayPort version	1.4
Supported graphics resolutions	3840 x 2160, 7680 x 4320
Maximum refresh rate	120 Hz
Number of shielding layers	3
AWG wire size	30
Data transfer rate	32.4 Gbit/s
Multi-Stream Transport (MST)	Yes
Colour sampling	4:4:4
Cable type	Round cable
Operational conditions	
Operating temperature (T-T)	0 - 50 °C
Certificates	
Compliance certificates	RoHS, TÜV mark
Weight & dimensions	
Cable diameter	6 mm

Weight	123 g
--------	-------

Packaging data

Package width	180 mm
---------------	--------

Package depth	180 mm
---------------	--------

Package height	25 mm
----------------	-------

Package weight	134 g
----------------	-------

Package type	Polybag
--------------	---------

Package volume	800 cm ³
----------------	---------------------

Logistics data

Country of origin	Taiwan
-------------------	--------

Other features

Depth	2500 mm
-------	---------

Height	13 mm
--------	-------

Width	21 mm
-------	-------

Matmenys ir svoris

Svoris	0,13kg
--------	--------