

ASUS ProArt Switch PQG-U1080 Unmanaged 2.5G Ethernet (100/1000/2500) Black

Gamintojas: **ASUS** · Modelis: **90IG0AF0-M09B00** · EAN: **4711636273176** · Prekės kodas: **735689**



168,90 €

Kaina su PVM

Be PVM: **139,59 €**

Sandėlyje




Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Creator-centric, minimalist design with flexible mounting options fits clean, professional studio setups
- ✓ Works with ProArt routers to enable creator-first network optimization across connected creative devices
- ✓ Eight 2.5G RJ45 ports and two 10G SFP+ ports provide high-speed wired connectivity for large file transfers, storage, and streaming using existing CAT5e cables
- ✓ Connect 2.5G and 10G devices such as NAS and Wi-Fi 7 access points to build a future-ready creator studio network
- ✓ True plug-and-play setup enables quick, intuitive expansion for creator studios and easy configuration



Aprašymas

Creator-First Networking

The ProArt Switch PQG-U1080 features eight 2.5G RJ45 ports and two 10G SFP+ ports to deliver high-speed wired expansion for creator studios, enabling stable connections, large file transfers, backup workflows and multi-device collaboration for network-attached storage (NAS), workstations, and other devices. Plug-and-play setup and versatile mounting options make it easy to integrate into clean, modern workspaces.

Techninė specifikacija

Specifications	
Sandėlio grupė	> Netzwerk > Switches [+1607][-273]
Management features	
Switch type	Unmanaged
Ports & interfaces	
Basic switching RJ-45 Ethernet ports quantity	8
Basic switching RJ-45 Ethernet ports type	2.5G Ethernet (100/1000/2500)
Installed SFP modules quantity	0
Installed SFP+ modules quantity	2
Network	
Networking standards	IEEE 802.3ab, IEEE 802.3bz, IEEE 802.3u, IEEE 802.3x, IEEE 802.3az
10G support	Yes
Copper ethernet cabling technology	100BASE-TX, 1000BASE-T, 2500BASE-T
Cable types supported	Cat5e
Flow control support	Yes
Data transmission	
MAC address table	16000 entries
Forwarding rate	59.52 Mpps
Jumbo frames support	Yes
Jumbo frames	10000
Packet buffer memory	8 MB
Design	
Rack mounting	No
Stackable	No
Product colour	Black
Power	
Power source	DC
Power supply included	Yes
DC input voltage	12 V
Input current	1 A
Power over Ethernet (PoE)	
Power over Ethernet (PoE)	No

Operational conditions

Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-40 - 70 °C
Operating relative humidity (H-H)	10 - 90%
Storage relative humidity (H-H)	5 - 90%

Weight & dimensions

Width	180 mm
Depth	89.5 mm
Height	26 mm
Weight	260 g

Packaging content

Quick start guide	Yes
-------------------	-----

Packaging data

Package type	Box
Package width	215 mm
Package depth	125 mm
Package height	110 mm
Package weight	760 g

Matmenys ir svoris

Svoris	0,78kg
--------	--------