

InLine Network Switch 8-Port, 1Gb/s, Desktop, Metal, fanless, shielded ports

Gamintojas: **INLINE** · Modelis: **32308M** · EAN: **4043718257331** · Prekės kodas: **735830**



46,90 €

Kaina su PVM

Be PVM: **38,76 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Basic switching RJ-45 Ethernet ports quantity: 8
- ✓ MAC address table: 1000 entries
- ✓ Cat3, Cat4, Cat5, Cat5e

Aprašymas

Reliable gigabit data transmission: Eight RJ45 ports with 10/100/1000 Mb/s auto-negotiation enable a stable and fast LAN connection without manual configuration.

Maintenance-free operation: As an unmanaged switch, the device is completely plug-and-play. It reduces set-up effort and minimizes sources of error during operation.

Silent metal housing: The fanless design ensures silent operation. At the same time, the metal housing supports effective heat dissipation.

Flexible installation options: The compact desktop format and prepared wall mounting enable space-saving integration in different environments.

Stable network performance: Store-and-forward technology, flow control and a MAC address table with 8K entries support reliable data processing even with higher network loads.

The InLine® 8 Port Gigabit Switch is a reliable solution for expanding existing network structures. It enables the simple connection of multiple Ethernet end devices via eight RJ45 ports with 10/100/1000 Mb/s auto-negotiation. Operation is unmanaged and completely plug-and-play. No configuration is required. The fanless metal housing supports noiseless continuous operation and ensures efficient heat dissipation. The integrated store-and-forward technology and flow control in full-duplex and asymmetric mode contribute to stable and low-loss data transmission. The compact desktop design and the pre-punched mounting points on the underside allow the switch to be positioned flexibly or mounted on the wall. The automatic detection of transmission speeds and Auto MDI/MDIX simplify integration into existing LAN structures. The switch is designed for reliable use in wired networks.

IEEE802.3i 10Base-T

IEEE802.3u 100Base-TX

IEEE802.3ab 1000Base-T
CSMA/CD
TCP/IP
IEEE802.3x Flow-Control full duplex
IEEE802.3z Flow-Control asymmetric
Backbone bandwidth 1 Gb/s
Forwarding rate 10Base-T 14880 pps/port
Forwarding rate 100Base-TX 148800 pps/port
MAC address table 8K
Auto MDI/MDIX
External power supply 5.0 V / 1.0 A

Techninė specifikacija

Specifications	
Sandėlio grupė	> Netzwerk > Switches [+1607][-273]
Ports & interfaces	
Basic switching RJ-45 Ethernet ports quantity	8
Basic switching RJ-45 Ethernet ports type	Gigabit Ethernet (10/100/1000)
Network	
Networking standards	IEEE 802.3, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z
10G support	No
Cable types supported	Cat3, Cat4, Cat5, Cat5e
Full duplex	Yes
Flow control support	Yes
Auto MDI/MDI-X	Yes
Ethernet LAN data rates	10,100,1000 Mbit/s
Auto-negotiation	Yes
MAC address auto-learning supported	Yes
Data transmission	
MAC address table	1000 entries
Forwarding rate	0.1488 Mpps
Packet forwarding rate (100 Mbps)	148800 pps
Packet forwarding rate (10 Mbps)	14880 pps
Design	
Product colour	Black
LED indicators	LAN, Power
Wall mountable	Yes

Performance

Maximum data transfer rate	1000 Mbit/s
----------------------------	-------------

Power

Input current	0.5 A
---------------	-------

Power over Ethernet (PoE)

Power over Ethernet (PoE)	No
---------------------------	----

Other features

Dimensions (WxDxH)	145 x 4.09 x 75 mm
--------------------	--------------------

Ethernet interface type	Fast Ethernet, Gigabit Ethernet
-------------------------	---------------------------------

Ethernet LAN (RJ-45) ports	8
----------------------------	---

Operational conditions

Operating temperature (T-T)	0 - 40 °C
-----------------------------	-----------

Storage temperature (T-T)	-40 - 70 °C
---------------------------	-------------

Operating relative humidity (H-H)	10 - 90%
-----------------------------------	----------

Storage relative humidity (H-H)	5 - 90%
---------------------------------	---------

Weight & dimensions

Width	145 mm
-------	--------

Depth	4.09 mm
-------	---------

Height	75 mm
--------	-------

Weight	2.8 kg
--------	--------

Packaging data

Package width	60 mm
---------------	-------

Package depth	190 mm
---------------	--------

Package height	140 mm
----------------	--------

Package weight	303 g
----------------	-------

Matmenys ir svoris

Svoris	0,50kg
--------	--------