

Lindy 15m DisplayPort 1.2 Cable, Gold Line

Gamintojas: **LINDY** · Modelis: **36297** · EAN: **4002888362979** · Prekės kodas: **735862**



191,91 €

Kaina su PVM

Be PVM: **158,60 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ No compromise, ultimate performance DisplayPort cable for demanding environments and mission critical systems
- ✓ Supports UHD resolutions up to 4096x2160@30Hz 4:4:4 8bit
- ✓ Full metal 24K gold plated housing, 24K gold plated connectors and contacts
- ✓ Low attenuation triple shielded cable, corrosion resistant, high performance OFC 24AWG conductors
- ✓ DisplayPort 1.2 compliant: 3D, 4K, 10.8Gbps, DisplayPort Certified; 25 year warranty



Aprašymas

From the Lines cable connectivity concept developed by Lindy, Gold Line DisplayPort cables are the no compromise, high performance connection solution for use in the most demanding professional environments.

Gold Line DisplayPort cables feature triple shielded construction with 24AWG OFC conductors for premium performance and corrosion resistance. High quality 24K gold plated contacts and connectors maintain optimal signal integrity and maximum reliability.

UHD resolutions up to 4K 4096x2160@30Hz 4:4:4 8bit, including stereoscopic 3D and HDCP are supported. DisplayPort 1.2 technology and DisplayPort compliance certification ensures compatibility with all DisplayPort enabled devices.

These superior quality cables utilise a unique low attenuation design that ensures consistent and reliable transmission even over very long

distances.

Gold DisplayPort cables are available in lengths from 0.5m to 20m.

Techninė specifikacija

Specifications	
Sandėlio grupė	> Kabel und Adapter > Displayport Kabel und Adapter [+1987][131]
Features	
Cable length	15 m
Connector 1	DisplayPort
Connector 2	DisplayPort
Connector 1 gender	Male
Connector 2 gender	Male
Maximum resolution	4096 x 2160 pixels
Product colour	Gold
Connector 1 form factor	Straight
Connector 2 form factor	Straight
Connector contacts plating	Gold
DisplayPort version	1.2
Supported graphics resolutions	4096 x 2160
Maximum refresh rate	30 Hz
3D	Yes
Magnetically shielded	Yes
Jacket material	Polyvinyl chloride (PVC)
AWG wire size	24
Data transfer rate	10.8 Gbit/s
Operational conditions	
Operating temperature (T-T)	-20 - 80 °C
Storage temperature (T-T)	-25 - 80 °C
Certificates	
Compliance certificates	REACH, RoHS
Weight & dimensions	
Cable diameter	9 mm
Packaging data	
Package type	Polybag

Logistics data	
Harmonized System (HS) code	84733080
Sustainability	
Sustainability compliance	Yes
Matmenys ir svoris	
Svoris	1,82kg