

TP-Link VIGI C440-W Kubas IP apsaugos kamera Lauke 2560 x 1440 pikseliai Lubos / siena

Gamintojas: **TP-LINK** · Modelis: **VIGI C440-W(4MM)** · EAN: **4897098683743** · Prekės kodas: **736159**



113,90 €

Kaina su PVM

Be PVM: **94,13 €**

Sandėlyje




Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Lauke IP apsaugos kamera
- ✓ CMOS 25,4 / 3 mm (1 / 3") 4 MP 2560 x 1440 pikseliai
- ✓ Vielinis ir Bevielis Ethernet LAN jungtis „Wi-Fi“
- ✓ Naktinis matymas 30 m
- ✓ Kubas Lubos / siena
- ✓ Balta



Aprašymas

All The Colors, All The Time

4MP Full-Color Wi-Fi Turret Network Camera

- High Definition
- Full-Color
- Smart Detection
- Active Defense
- Two-Way Audio
- Onboard Storage
- Wired or Wireless Networking
- Smart Video Enhancement
- Remote Monitoring
- Smart Video Coding
- ONVIF Ensures Compatibility

Clarity and Colors, All in One

Monitor 24-hour clear and colorful details even in pitch dark night. VIGI Full-Color camera provides maximum 4MP resolutions and ensures colorful monitoring with its large-aperture lens, high-sensitivity sensor, and attached supplemental lights.

Simple and Fast

Wireless Connection

Enjoy simple wiring with Wi-Fi signals. Just power up your camera, then the transmission starts with its built-in 2x2 MIMO antennas.

We keep an eye on your business.

Smart Detection

Receive notifications and check feeds when someone crosses a boundary, enters an area you've set, or obstructs the camera.

Motion Detection

Get instant notifications when your camera detects motion.

Area Intrusion

Set customized activity zones around key areas for more focused monitoring.

Line-Crossing

Set a boundary and receive an alert anytime a person crosses it from either or both directions.

Camera Tampering

Receive alerts when someone obstructs the camera.

Active Defense

Warn and expel potential intruders instantly with sound and light alarms when abnormal events are detected.

Every Event is Under Your Control.

VIGI cameras intelligently detects activities, inform you instantly and respond automatically by smart detection and two-way audio.

Never miss a detail.

SmartVid-Smart Video Enhancement

Smart IR

Keeps objects from being under-rendered when far away or overexposed when close to camera at night.

Wide Dynamic Range

Adjusts for lighting contrast to minimize shadowing effects and renders images true to life.

3D DNR

Removes abnormal pixelation to provide clearer video and eliminate distortion.

More compression. More savings. Same quality.

Without using any extra bandwidth, your cameras transmit compressed crystal-clear video to save disk space, ease network loads, and reduce monitoring costs without sacrificing image quality.

Flexible Management and Storage

Take full control over your security via three management methods, VIGI NVR, App, and Security Manager. Local storage is available for each method, as well as onboard storage with SD card slot.

Flexible Installation Gives You More Convenience.

Easily route your camera's cable into a dropped ceiling or avoid drilling by slotting it through the camera's side outlet.

One system. Full security.

Run your business with peace of mind.

The VIGI professional surveillance system by TP-Link is dedicated to protecting the business you've worked hard to build — whenever, wherever. Our outstanding functions, reliable quality guarantees, and simplified installation work together to ensure your business stays safe and sound.

Techninė specifikacija

Veikimo charakteristikos

Tipas	IP apsaugos kamera
Talpinimas palaikomas	Lauke
Ryšio technologija	Vielinis ir Bevielis
Sertifikavimas	CE, RCM, BSMI, VCCI, RoHS, NTRA, KC

Konstrukcija

Montavimo tipas	Lubos / siena
Produkto spalva	Balta
Forma	Kubas
LED indikatoriai	Taip
Korpuso medžiaga	Plastikas

Fotoaparatas

Kameros panoramavimo valdymas	Taip
Kameros pakėlimo valdymas	Taip
Minimalus apšviestumas	0 lx
Sukimosi kampas	360°

Objektyvo vaizdo kampas, horizontalus	79°
Objektyvo vaizdo kampas, vertikalus	43°
Objektyvo vaizdo kampas, įstrižainė	93°
Posvyrio kampo intervalas	0 - 85°
Viso diapozonas	0 - 360°
Vaizdo jutiklis	
Jutiklio tipas	CMOS
Jutiklių skaičius	1
Optinio sensoriaus dydis	25,4 / 3 mm (1 / 3")
Panoraminė kamera	
Skaitmeninis platus dinaminis diapazonas (DWDR) (panoraminė kamera)	Taip
Lęšių sistema	
Fiksuotas fokusavimas	Taip
Maksimalus apertūros skaičius	1,6
Naktinis matymas	
Naktinis matymas	Taip
Naktinio matymo atstumas	30 m
Video	
Maksimali rezoliucija	2560 x 1440 pikseliai
Iš viso megapikselių	4 MP
Video suspaudimo formatai	H.265+, H.264, H.264+, H.265
Palaikomos grafikos rezoliucijos	2048 x 1280, 2304 x 1296, 2560 x 1440, 1920 x 1080 (HD 1080)
Palaikomi vaizdo režimai	1080p, 1440p
Vaizdo įrašymas	Taip
Vaizdo transliavimas	Taip
Triukšmo mažinimas	Taip
Triukšmo sumažinimo technologija	3D triukšmo mažinimas
Vaizdo kokybės koregavimas	Ryškumas, Kontrastas, Veidrodis
Tinklas	
Ethernet LAN jungtis	Taip
„Wi-Fi“	Taip
Bluetooth	Ne
Eterneto sąsajos tipas	Greitas ethernetas
Tinklo standartai	IEEE 802.11n, IEEE 802.11b, IEEE 802.11g

Wi-Fi standartai	802.11b, 802.11g, Wi-Fi 4 (802.11n)
Belaidis LAN duomenų perdavimo greitis (maks.)	150 Mbit/ai
Laikmenos	
Integruotas kietasis diskas	Ne
Integruotas kortelių skaitytuvas	Taip
Suderinamos atminties kortelės	MicroSD (TransFlash)
Ryšys	
Ethernet LAN (RJ-45) portų kiekis	1
Energijos valdymas	
Maitinimo šaltinio tipas	DC
Aplinkos sąlygos	
Darbo temperatūros diapazonas (TT)	-30 - 60 °C
Svoris ir matmenys	
Plotis	123 mm
Ilgis	123 mm
Aukštis	84 mm
Pakuotės duomenys	
Pakuotės plotis	163 mm
Pakuotės gylis	208 mm
Pakuotės aukštis	116 mm
Paketo svoris	530 g
Pakuotės turinys	
Fotoaparatus skaičius	1
Instrukcija	Taip
Matmenys ir svoris	
Matmenys (I × P × A)	16,00cm × 21,00cm × 12,00cm
Svoris	0,53kg

Dokumentai ir vaizdo įrašai

- › [Naudojimo instrukcija](#)
- › [Greitos pradžios vadovas](#)
- › [Gaminio lankstinukas](#)

Gamintojo ir saugos informacija

GAMINTOJAS

TP-Link

ATSAKINGAS ASMUO ES

TP-Link Deutschland GmbH

Niederkasseler Lohweg 175, 40547 Düsseldorf,
DE

tp-link.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt