

Lindy 32622 power distribution unit (PDU) 4 AC outlet(s) 1U Black

Gamintojas: **LINDY** · Modelis: **32622** · EAN: **4002888326223** · Prekės kodas: **736502**



269,90 €

Kaina su PVM

Be PVM: **223,06 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Remote power management switch for up to 4 devices
- ✓ Control via intuitive web GUI, RS232 and API commands
- ✓ Individual power control and monitoring (voltage, current and consumption)
- ✓ 4x IEC C13 10A output ports



Aprašymas

The Lindy IPower Switch is a compact and intelligent power management solution designed for IT, AV, industrial, and small office environments. It connects to a network infrastructure to provide remote control and monitoring of up to four connected devices such as servers, workstations, hubs, and routers. Users can easily perform power-on, power-off, and reboot functions either through a user-friendly web interface or external control commands.

Each output can be individually configured with power-on and power-off delay settings, allowing precise sequencing after a power outage or system reset.

Supports total power of 2500W, A current range from 0A to 10A with a Voltage range from 110V to 250V.

Each outlet has its own status indication LED and button to allow the manual management function (not active by default). From the web GUI it is possible to manage the complete configuration of the unit, monitor the status of each outlet port, schedule on/off status and so on. Open APIs for Telnet, Modbus TCP, SSH, SNMP and MQTT protocols are supported, while security and network settings are provided to cover most of the

requirements needed in demanding applications.

The user can also configure email notifications to receive alerts and reports directly, including warnings about overload and overcurrent thresholds.

Ideal for IT administrators, system integrator, and AV installers, the Lindy IPower Switch delivers reliable, flexible, and secure power control for critical applications.

Techninė specifikacija

Specifications	
Sandėlio grupė	> Netzwerk > Switches [+1607][-273]
Design	
PDU types	Metered, Switched
Rack capacity	1U
Housing material	Metal
Product colour	Black
Ports & interfaces	
AC outlets quantity	4 AC outlet(s)
AC outlet types	C13 coupler
Power plug	C14 coupler
Serial ports quantity	1
Ethernet LAN (RJ-45) ports	2
Management features	
Monitoring	Voltage, Current, Power
Power	
Nominal input voltage	110 - 250 V
Maximum current	10 A
AC input frequency	50/60 Hz
Power protection features	Over voltage, Over current
Maximum power	2500 W
Certificates	
Compliance certificates	CE, UKCA, RoHS, REACH, Electromagnetic Compatibility (EMC), Low Voltage Directive (LVD), Federal Communications Commission (FCC)
Operational conditions	
Operating temperature (T-T)	-10 - 55 °C
Storage temperature (T-T)	-20 - 70 °C
Operating relative humidity (H-H)	0 - 95%

Weight & dimensions

Width	218 mm
Depth	153 mm
Height	42.5 mm
Weight	1.7 kg

Packaging content

Cables included	Power, Serial
Manual	Yes

Packaging data

Package weight	2.7 kg
Package width	355 mm
Package depth	240 mm
Package height	55 mm

Matmenys ir svoris

Svoris	2,06kg
--------	--------