

Lindy 36516 DisplayPort cable 1 m Black

Gamintojas: **LINDY** · Modelis: **36516** · EAN: **4002888365161** · Prekės kodas: **736504**



23,90 €

Kaina su PVM

Be PVM: **19,75 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Entry level DisplayPort 2.1 cable for home and small office applications
- ✓ Supports resolutions up to 16K@60Hz 4:4:4 10-Bit with DSC (Display Screen Compression)
- ✓ Robust ABS housing 24K gold plated connectors and contacts
- ✓ Triple shielded cable, corrosion resistant Bare Copper 28AWG conductors



Aprašymas

From the Lines cable connectivity concept developed by Lindy, Black Line DisplayPort 2.1 cables are fully featured, entry level high resolution connection solutions, perfect for home and small office use.

UHD resolutions up to 16K 15360x8640@60Hz 4:4:4 10-Bit With DSC (Display Screen Compression). DSC is a visually lossless compression standard that allows higher resolutions and refresh rates by reducing the data bandwidth required for transmission. Black Line DisplayPort cables are also capable of transmitting 32 channel audio and Dolby True HD.

Black Line DisplayPort cables feature triple shielded construction with 28AWG copper conductors for performance and corrosion resistance. Nickel connectors and 24K gold plated contacts maintain signal integrity and reliability.

Techninė specifikacija

Specifications	
Sandėlio grupė	> Kabel und Adapter > Displayport Kabel und Adapter [+1987][-131]
Features	
Cable length	1 m
Connector 1	DisplayPort
Connector 2	DisplayPort
Connector 1 gender	Male
Connector 2 gender	Male
Maximum resolution	16360 x 8640 pixels
Product colour	Black
Connector 1 form factor	Straight
Connector 2 form factor	Straight
Connector contacts plating	Nickel
DisplayPort version	2.1
Maximum refresh rate	60 Hz
Jacket material	Polyvinyl chloride (PVC)
Connector housing material	Acrylonitrile butadiene styrene (ABS)
AWG wire size	28
Bandwidth	54000 MB/s
Cable type	Round cable
Nominal attenuation	100 MHz - 450 MHz < 5.1 dB 450 MHz - 8100 MHz < 33.28 dB 8100 MHz - 13500 MHz < 38.0 dB
Operational conditions	
Operating temperature (T-T)	-20 - 80 °C
Storage temperature (T-T)	-25 - 85 °C
Certificates	
Compliance certificates	RoHS, REACH, UL
Weight & dimensions	
Cable diameter	7 mm
Connector 1 dimensions (WxDxH)	20.7 x 42.6 x 13 mm
Packaging data	
Package type	Polybag
Packaging content	

Quantity per pack	1 pc(s)
-------------------	---------

Matmenys ir svoris

Svoris	0,08kg
--------	--------