

ACT 4-Port DisplayPort 4K@60Hz KVM switch (AC7934)

Gamintojas: **ACT** · Modelis: **AC7934** · EAN: **8716065589825** · Prekės kodas: **736549**



195,90 €

Kaina su PVM

Be PVM: **161,90 €**

Sandėlyje




Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 4-Port 4K@60Hz DisplayPort KVM Switch: control four computers with a single monitor, USB keyboard and mouse
- ✓ Supports a resolution up to 3840x2160 (4K) @60Hz, 4:4:4 12-bit, DisplayPort 1.4a, HDCP 2.2 compliant
- ✓ 4 USB-A ports 5Gbps for peripheral sharing
- ✓ Control the KVM switch with the front panel select button, IR remote control, keyboard hotkeys, mouse or RS-232 commands
- ✓ Supports Multi-Stream Transport (MST) daisy chaining on DisplayPort with a bandwidth of 32.4Gbps
- ✓ Dual-Mode DisplayPort technology (DP++) supports passive HDMI and DVI adapters
- ✓ Supplied with DisplayPort cables, USB-B cables, remote control, IR receiver, RS-232 connector and mounting brackets
- ✓ Power supply included (12V / 1A / 12W); secure locked power connection



Aprašymas

The AC7934 4-port DisplayPort KVM switch controls four computers while using a single DisplayPort monitor, single USB keyboard and mouse. The DisplayPort output supports a monitor with a resolution up to 4K@60Hz. The AC7934 lets you switch between computers using the buttons on the switch itself, the IR remote control, keyboard hotkeys, a mouse, or RS-232 commands. The AC7934 has a solid metal housing and comes with all needed cabling.

Control four computers with a single DisplayPort monitor, keyboard and mouse

Simplify your workspace by connecting four computers to the AC7934 via DisplayPort. Connect a single DisplayPort monitor and a keyboard and

mouse set to the switch and control all host devices with minimal setup.

Supports up to 4K @ 60Hz

The AC7934 DisplayPort KVM switch supports 4K resolution at 60Hz with 4:4:4 12 bit color. The KVM switch complies with DisplayPort 1.4a and HDCP 2.2 standards.

Easy switching between computers

Switching between four connected computers is easy with the dedicated button on the AC7934 KVM switch. Or use IR control, a mouse, keyboard shortcuts or RS-232 commands.

Supports MST daisy chaining

The AC7934 supports both SST (Single Stream Transport) and MST (Multi Stream Transport) via daisy chaining. Connect additional monitors via DisplayPort MST daisy chaining to extend your desktop across multiple screens (depending on total bandwidth and source capabilities).

Dual-Mode DisplayPort DP++ support

Dual-Mode DisplayPort (DP++) ensures compatibility with passive HDMI and DVI adapters.

Additional features

The AC7934 includes four USB 3.2 Gen1 (USB 3.0) 5Gbps ports for sharing peripherals, such as a keyboard, mouse, printer and more. The switch includes 4x DisplayPort cables, 4x USB-B cables, remote control, IR receiver, RS-232 connector and mounting brackets with screws.

Prevent accidental power cord disconnection

The power connection on the KVM switch is secured with a screw lock to prevent accidental disconnection.

User scenarios

Government offices: Control sensitive systems that are isolated from the network.

Datacenters and server rooms: Troubleshoot, update and maintain servers.

Home office: switch easily between workstations with only one monitor, mouse, keyboard setup.

Corporate: IT professionals can manage multiple work PCs, servers or virtual machines.

Control rooms, labs and technical facilities: Ideal for critical environments where operators need access to multiple PCs.

Techninė specifikacija

Specifications	
Sandėlio grupė	> Kabel und Adapter > Displayport Kabel und Adapter [+1987][-131]
Ports & interfaces	
Number of computers controlled	4
Keyboard port type	USB
Mouse port type	USB
Video port type	DisplayPort
Console ports	DisplayPort, USB A
DisplayPorts quantity	5
DisplayPort version	1.4a
USB 3.2 Gen 1 (3.1 Gen 1) Type-B ports quantity	4
DC-in jack	Yes

Performance

HD type	4K Ultra HD
Maximum resolution	4096 x 2160 pixels
Video bandwidth	60 Hz
Data transfer rate (max)	32.4 Gbit/s
HDCP	Yes
Daisy chain	Yes
Maximum refresh rate	129 Hz
HDCP version	2.2

Design

Rack mounting	No
Product colour	Black
LED indicators	Yes
Hot keys	Yes

Display

Built-in display	No
------------------	----

Power

Power source	DC
Input voltage	12 V
Input current	1 A
Power consumption (typical)	12 W
External power adapter	Yes

Packaging content

Cables included	IR, DisplayPort, USB Type-A to USB Type-B
AC adapter included	Yes
Remote control included	Yes

Matmenys ir svoris

Svoris	1,00kg
--------	--------