

ATEN USB DisplayPort Dual View HDBaseT™ 2.0 KVM Extender (4K@100m for Single View)

Gamintojas: **ATEN** · Modelis: **CE924-AT-G** · EAN: **4710469340611** · Prekės kodas: **736824**



1 280,91 €

Kaina su PVM

Be PVM: **1 058,60 €**

Sandėlyje




Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Allows dual view DisplayPort access to a computer and KVM control from a remote console
- ✓ Extends video, audio, USB, and RS-232 signals via a single Cat 6 / 6a / 2L-2910 Cat 6 cable
- ✓ Supports 4 ports USB 2.0 full speed hub on the receiver-allowing to connect up to 4 various USB 2.0 peripheral
- ✓ Long distance with superior video quality
- ✓ HDBaseT™ Standard mode up to 4K @ 100 m (Cat 6 / 6a / 2L-2910); (single view only; dual-view resolution up to 1080P)
- ✓ HDBaseT™ Long-Reach mode up to 1080P @ 150 m (single view only; dual-view resolution up to 720P)



Aprašymas

The ATEN CE924 USB DisplayPort Dual View HDBaseT™ 2.0 KVM Extender integrates the latest HDBaseT™ 2.0 technologies to deliver 4K video, stereo audio, USB, and RS-232 signals. The HDBaseT™ 2.0 guarantees the most reliable transmission on the market as well as it provides long-reach capability that extends Full HD 1080P signals up to 150 meters. In addition, CE924 supports single 4K display or dual 1080p display for DisplayPort video output resolution up to 100m by using a single Cat6 / 2L-2910 Cat 6 cable.

With an easy cable installation supporting various signals, the CE924 is ideal for applications where convenient remote access is required – such as transportation control centers, medical facilities, industrial warehouses, and extended workstations.

1x CE924L USB DisplayPort Dual View HDBaseT 2.0 KVM Extender (Local Unit)

1x CE924R USB DisplayPort Dual View HDBaseT 2.0 KVM Extender (Remote Unit)
2x DisplayPort cables
1x pink audio jack cable set
1x green audio jack cable set
1x USB Type-A to Type-B cable
2x power adapters
2x mounting kits
1x user instructions

Techninė specifikacija

Specifications	
Sandėlio grupė	> Kabel und Adapter > Displayport Kabel und Adapter [+1987][-131]
Features	
Type	Transmitter & receiver
Connectivity technology	Wired
Maximum digital resolution	4096 x 2160 pixels
Product colour	Black
Material	Metal
LED indicators	Yes
Transmitter	
Transmitter video port type	DisplayPort
RJ-45 ports quantity (transmitter)	1
Receiver	
Receiver local video port type	DisplayPort
RJ-45 ports quantity (receiver)	1
Ports & interfaces	
USB port type	USB Type-A
Weight & dimensions	
Transmitter width	15.4 cm
Transmitter depth	17.4 cm
Transmitter height	2.88 cm
Transmitter weight	820 g
Receiver width	15.6 cm
Receiver depth	17.4 cm
Receiver height	2.88 cm
Receiver weight	850 g

Packaging data

Package width	131 mm
Package depth	540 mm
Package height	233 mm
Package weight	4.04 kg

Packaging content

AC adapter included	Yes
Cables included	DisplayPort, USB Type-A to USB Type-B

Operational conditions

Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-20 - 60 °C
Operating relative humidity (H-H)	0 - 80%
Storage relative humidity (H-H)	0 - 80%

Technical details

Weight	3.08 kg
--------	---------

Logistics data

Master (outer) case net weight	3.08 kg
Harmonized System (HS) code	84733080
Master (outer) case width	247 mm
Master (outer) case length	556 mm
Master (outer) case height	153 mm
Master (outer) case gross weight	4.28 kg
Products per master (outer) case	1 pc(s)

Matmenys ir svoris

Svoris	3,56kg
--------	--------