

LevelOne Hilbert 10-Port Gigabit PoE Smart Lite Switch, 8 PoE Outputs, 2 x Gigabit SFP, 802.3at/af PoE, 130W PoE Power Budget

Gamintojas: **LEVELONE** · Modelis: **GES-2110P** · EAN: **4015867229217** · Prekės kodas: **736902**



208,89 €

Kaina su PVM

Be PVM: **172,64 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 8 PoE-Plus Gigabit Ethernet ports supports PoE Watchdog and 2 Gigabit SFP slots
- ✓ Total PoE power budget: 130W, up to 30W per port
- ✓ IEEE 802.3af/at PoE compliant to simplify deployment and installation
- ✓ Supports 8K MAC address auto-learning and auto-aging
- ✓ 9K jumbo frames to increase data transfer rates
- ✓ IP Multicast Filtering through IGMP Snooping V1 / V2
- ✓ 802.1Q tag-based VLAN allows network segmentation to enhance performance and security
- ✓ IEEE 802.1p QoS with 4 priority queues
- ✓ Supports unknown unicast / broadcast / multicast storm control
- ✓ Minimize carbon footprint with advanced energy efficient technology (IEEE 802.3az)



Aprašymas

"The LevelOne GES-2110P Hilbert gigabit PoE smart lite switch is a next-generation Ethernet Switch offering powerful better PoE functionality and usability that delivers the cost-effectively business and transports Ethernet services via fiber or copper connections. GES-2110P delivers 8 (10M/100M/1G) RJ45/PoE+ (Support 802.3at/af, and total up to 130W) ports and 2 Gigabit SFP ports. can be matched with the latest LevelOne IP Locator, the software is the easiest to use switch discovery tool, it can search all Hilbert series switches, instantly know the forgotten IP and other info. Compatible with mainstream Windows and Mac operating systems.

The LevelOne GES-2110P provides high HW performance and environment flexibility for Enterprises. GES-2110P is ideal to deliver management simplicity, optimum user experience, and lower total cost of ownership.

Techninė specifikacija

Specifications	
Sandėlio grupė	> Netzwerk > Switches [+1607][-273]
Management features	
Switch type	Managed
Switch layer	L2
Quality of Service (QoS) support	Yes
Web-based management	Yes
Ports & interfaces	
Basic switching RJ-45 Ethernet ports quantity	8
Basic switching RJ-45 Ethernet ports type	Gigabit Ethernet (10/100/1000)
Installed SFP modules quantity	0
Installed SFP+ modules quantity	0
Gigabit Ethernet (copper) ports quantity	8
SFP module slots quantity	2
Network	
Networking standards	IEEE 802.1Q, IEEE 802.1p, IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3az, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z
10G support	No
Copper ethernet cabling technology	10BASE-T, 100BASE-TX, 1000BASE-T
Port mirroring	Yes
Full duplex	Yes
Flow control support	Yes
Link aggregation	Yes
Broadcast storm control	Yes
Rate limiting	Yes
MAC address auto-learning supported	Yes
MAC address auto-aging supported	Yes
VLAN support	Yes
Virtual LAN features	Tagged VLAN
Number of VLANs	32
Data transmission	

MAC address table	8000 entries
Switching capacity	20 Gbit/s
Number of queues	4
Jumbo frames support	Yes
Jumbo frames	9000
Packet buffer memory	4.1 MB
Security	
IGMP snooping	Yes
Multicast features	
Multicast support	Yes
Design	
Rack mounting	No
Product colour	Black
LED indicators	Activity, Link, PoE
Performance	
Flash memory	2 MB
Noise level	0 dB
Fanless	Yes
Mean time between failures (MTBF)	43800 h
Power	
Power source	AC/PoE
AC input voltage	100 - 240 V
AC input frequency	50 - 60 Hz
Power consumption (max)	150 W
Surge protection	Yes
Surge protection voltage	8 kV
Power over Ethernet (PoE)	
Power over Ethernet (PoE)	Yes
Power over Ethernet plus (PoE+) ports quantity	8
Power over Ethernet (PoE) power per port	30 W
Total Power over Ethernet (PoE) budget	130 W
Operational conditions	
Operating temperature (T-T)	0 - 45 °C
Storage temperature (T-T)	-40 - 70 °C

Operating relative humidity (H-H)	10 - 90%
Storage relative humidity (H-H)	5 - 95%
Heat dissipation	40.94 BTU/h
Weight & dimensions	
Width	271 mm
Depth	181.5 mm
Height	44.5 mm
Weight	1.2 kg
Packaging content	
Cables included	AC
Quick start guide	Yes
Rack mount kit	Yes
Packaging data	
Package type	Box
Package width	350 mm
Package depth	267 mm
Package height	89 mm
Package weight	1.75 kg
Technical details	
Master (outer) cases per pallet (air)	12 pc(s)
Pallet gross length	80 cm
Pallet gross width	120 cm
Pallet height (air)	182.4 cm
Certificates	
Compliance certificates	CE, RoHS
Certification	UKCA, FCC Class A
Logistics data	
Master (outer) case net weight	1 kg
Country of origin	China
Master (outer) case width	480 mm
Master (outer) case length	370 mm
Master (outer) case height	560 mm
Master (outer) case gross weight	18.5 kg
Products per master (outer) case	10 pc(s)

Sustainability	
Sustainability compliance	Yes
Matmenys ir svoris	
Svoris	1,68kg