

TP-Link Omada 24-Port 10GBASE-T L2+ Managed Switch with 8 10GE SFP+ Slots

Gamintojas: **TP-LINK** · Modelis: **SX3832** · EAN: **8885020622652** · Prekės kodas: **737021**



1 420,90 €

Kaina su PVM

Be PVM: **1 174,30 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 24× 1/2.5/5/10 Gbps RJ45 ports
- ✓ 8× 1/10 Gbps SFP+ slots
- ✓ 640 Gbps switching capacity
- ✓ Centralized cloud management via the web or the Omada app†
- ✓ Standalone management via web, CLI, SNMP, and RMON
- ✓ Static Routing helps route internal traffic for higher efficiency
- ✓ VLAN, ACL, QoS, IGMP Snooping, OAM, and DDM
- ✓ ERPS supports rapid protection and recovery in a ring topology
- ✓ Durable metal casing and rack-mountable design



Aprašymas

Omada 24-Port 10GBASE-T L2+ Managed Switch with 8 10GE SFP+ Slots

- 24× 1/2.5/5/10 Gbps RJ45 Ports
- 8× 10 Gbps SFP+ Slots
- Centralized Management
- Omada App

- Zero-Touch Provisioning
- Ethernet Ring Protection Switching
- Static Routing
- Traffic Separation

Techninė specifikacija

Specifications	
Sandėlio grupė	> Netzwerk > Switches [+1607][-273]
Management features	
Switch type	Managed
Switch layer	L2/L2+
Quality of Service (QoS) support	Yes
Web-based management	Yes
Cloud-managed	Yes
ARP inspection	Yes
Configuring Location Settings (CLI)	Yes
System event log	Yes
Ports & interfaces	
Basic switching RJ-45 Ethernet ports quantity	24
Basic switching RJ-45 Ethernet ports type	10G Ethernet (100/1000/10000)
SFP+ module slots quantity	8
USB Type-C ports quantity	1
Console port	RJ-45/USB Type-C
Network	
Networking standards	IEEE 802.3az
10G support	Yes
Port mirroring	Yes
IP routing	Yes
Flow control support	Yes
Broadcast storm control	Yes
Rate limiting	Yes
Spanning tree protocol	Yes
Ethernet LAN data rates	10,100 Mbit/s
VLAN support	Yes
Virtual LAN features	MAC address-based VLAN, Multicast VLAN, Private VLAN, Voice VLAN

Data transmission

MAC address table	32000 entries
Switching capacity	640 Gbit/s
Forwarding rate	240 Mpps
Static route	Yes
Jumbo frames support	Yes
Jumbo frames	9000
Packet buffer memory	24 MB

Security

DHCP features	DHCP relay, DHCP server, DHCP snooping, DHCPv6 snooping
Access Control List (ACL)	Yes
IGMP snooping	Yes
SSH/SSL support	Yes
Loop protection	Yes
Authentication	Auto VLAN, MAC-based authentication, Port-based authentication
Authentication type	AAA, RADIUS, TACACS+

Multicast features

Multicast support	Yes
-------------------	-----

Design

Rack mounting	Yes
Stackable	Yes
Form factor	1U
Product colour	Black
LED indicators	Yes
Number of fans	2 fan(s)

Power

Power source	AC
Power supply included	Yes
AC input voltage	100 - 240 V
AC input frequency	50/60 Hz
Power consumption (max)	106.5 W

Power over Ethernet (PoE)

Power over Ethernet (PoE)	No
---------------------------	----

Operational conditions

Operating temperature (T-T)	-5 - 50 °C
Storage temperature (T-T)	-40 - 70 °C
Operating relative humidity (H-H)	10 - 90%
Storage relative humidity (H-H)	5 - 90%
Heat dissipation	363.23 BTU/h
Weight & dimensions	
Width	440 mm
Depth	220 mm
Height	44 mm
Packaging content	
Cables included	AC, LAN (RJ-45)
Quick start guide	Yes
Rack mount kit	Yes
Matmenys ir svoris	
Matmenys (I × P × A)	54,00cm × 34,00cm × 10,00cm
Svoris	4,40kg