

LevelOne 8-Port Fast Ethernet Industrial Switch, DIN-Rail, -40°C to 75°C

Gamintojas: **LEVELONE** · Modelis: **IFS-0801** · EAN: **4015867223932** · Prekės kodas: **737497**



85,90 €

Kaina su PVM

Be PVM: **70,99 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Provides flexibility of 8 x 10/100BASE-TX ports
- ✓ Provides DIN-rail, wall or desktop mounting
- ✓ 10/100Mbps, full/half-duplex, auto-negotiation, auto-MDI/MDIX
- ✓ Redundant power inputs with Terminal Block

Aprašymas

LevelOne IFS-0801 Industry Ethernet Switch provides 8 ports 10/100Base network at mission-critical environment. With the industrial standard DIN-rail mount; this switch can be easily installed in the cabinet, plus the clearly visible status LEDs provide simple monitoring of port link activity.

Techninė specifikacija

Specifications

Sandėlio grupė > Netzwerk > Switches [+1607][-273]

Management features

Switch type Unmanaged

Ports & interfaces

Basic switching RJ-45 Ethernet ports quantity	8
Basic switching RJ-45 Ethernet ports type	Fast Ethernet (10/100)
Fast Ethernet (copper) ports quantity	8

Network

Networking standards	IEEE 802.3, IEEE 802.3u, IEEE 802.3x
10G support	No
Copper ethernet cabling technology	10BASE-T, 100BASE-TX
Full duplex	Yes
Half duplex	Yes
Flow control support	Yes
Auto MDI/MDI-X	Yes
Auto-negotiation	Yes

Data transmission

MAC address table	8000 entries
Switching capacity	1.6 Gbit/s
Packet buffer memory	1 MB

Design

Product colour	Black
LED indicators	Activity, Link, Power
Wall mountable	Yes
DIN rail mounting	Yes

Power

Power source	AC/DC
Power supply included	Yes
Input voltage	12 - 60 V
Surge protection	Yes
Surge protection voltage	8 kV

Power over Ethernet (PoE)

Power over Ethernet (PoE)	No
---------------------------	----

Other features

Terminal block port	Yes
---------------------	-----

Operational conditions

Operating temperature (T-T)	-40 - 75 °C
Storage temperature (T-T)	-40 - 85 °C
Operating relative humidity (H-H)	0 - 95%
Storage relative humidity (H-H)	0 - 95%

Weight & dimensions

Width	165 mm
Depth	114 mm
Height	50 mm
Weight	450 g
Packaging content	
Quick start guide	Yes
Packaging data	
Terminal block included	Yes
Certificates	
Compliance certificates	CE, Federal Communications Commission (FCC)
Sustainability	
Sustainability compliance	Yes
Matmenys ir svoris	
Svoris	0,94kg