

LevelOne KILBY 10-Port L2 Managed Gigabit Switch, 2 x SFP

Gamintojas: **LEVELONE** · Modelis: **GEL-1061** · EAN: **4015867228623** · Prekės kodas: **737560**



281,91 €

Kaina su PVM

Be PVM: **232,98 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 8 Gigabit Ethernet ports and 2 Gigabit SFP slots
- ✓ IEEE 802.1d/w/s Spanning Tree Protocol (STP) and port mirroring
- ✓ IEEE 802.1p QoS with 8 priority queues
- ✓ IEEE 802.3ad LACP for auto port aggregation
- ✓ IP Multicast Filtering through IGMP Snooping
- ✓ Supports port-based VLAN, IEEE 802.1Q VLAN Tagging
- ✓ Supports IPv4/IPv6 network operation
- ✓ 6KV surge protection, 6KV contact / 8KV air ESD protection



Aprašymas

The LevelOne GEL-1061 is an intelligent 10-Port L2 managed gigabit switch with 8 RJ45 ports and 2 SFP fiber slots, designed for enterprise or large workgroups connectivity applications with the non-blocking, wire-speed switching performance and advanced networking management functions.

The switch supports a flexible web-based management interface for both IPv4 and IPv6 as well as console, SNMP and Telnet management access. Despite its affordable pricing, the GEL-1061 is equipped with many advanced features such as Internet Group Management Protocol (IGMP) snooping, port-/MAC-/tag-based VLAN, IEEE 802.1d/w/s Spanning Tree, Access Control List (ACL), Link Aggregation Control Protocol (LACP), IEEE 802.1p QoS, Storm Control for protecting against broadcast/multicast/unknown unicast and much more.

An ideal network solution for anyone looking for an affordable and efficient way to expand their network.

Techninė specifikacija

Specifications	
Sandėlio grupė	> Netzwerk > Switches [+1607][-273]
Management features	
Switch type	Managed
Switch layer	L2
Quality of Service (QoS) support	Yes
Traffic classification	Yes
Ports & interfaces	
Basic switching RJ-45 Ethernet ports quantity	8
Basic switching RJ-45 Ethernet ports type	Gigabit Ethernet (10/100/1000)
SFP module slots quantity	2
Fiber optic connector	SFP
Console port	RJ-45
Power connector	AC-in jack
Network	
Networking standards	IEEE 802.1D, IEEE 802.1Q, IEEE 802.1p, IEEE 802.1s, IEEE 802.1w, IEEE 802.3, IEEE 802.3ab, IEEE 802.3ad, IEEE 802.3af, IEEE 802.3az, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z
10G support	No
Port mirroring	Yes
Flow control support	Yes
Link aggregation	Yes
Broadcast storm control	Yes
Rate limiting	Yes
Spanning tree protocol	Yes
Cable length detection	Yes
VLAN support	Yes
Virtual LAN features	Port-based VLAN, Tagged VLAN
Optical fiber	
Fiber ethernet cabling technology	100BASE-X, 1000BASE-X
Data transmission	
MAC address table	8000 entries
Switching capacity	20 Gbit/s

Throughput	14.9 Mpps
Number of queues	8
Jumbo frames support	Yes
Jumbo frames	9000
Packet buffer memory	1 MB
Security	
Access Control List (ACL)	Yes
IGMP snooping	Yes
MAC address filtering	Yes
Static port security	Yes
Design	
Rack mounting	Yes
Product colour	Black
Reset button	Yes
LED indicators	Activity, Link, Power
Performance	
Internal memory	128 MB
Flash memory	16 MB
Fanless	No
Minimum system requirements	CE RoHS
Power	
Power source	AC
Power supply included	Yes
AC input voltage	100 - 240 V
AC input frequency	50 - 60 Hz
Power consumption (typical)	15 W
Power over Ethernet (PoE)	
Power over Ethernet (PoE)	No
Operational conditions	
Operating temperature (T-T)	-10 - 50 °C
Storage temperature (T-T)	-40 - 85 °C
Operating relative humidity (H-H)	0 - 95%
Weight & dimensions	
Width	270 mm

Depth	181 mm
Height	44 mm
Weight	800 g
Packaging content	
Cables included	AC
Quick start guide	Yes
Packaging data	
Package type	Box
Package width	345 mm
Package depth	255 mm
Package height	82 mm
Package weight	2 kg
Logistics data	
Harmonized System (HS) code	85176990
Matmenys ir svoris	
Svoris	1,80kg