

TP-Link VIGI 4MP Outdoor Full-Color Bullet Network Camera

 Gamintojas: **TP-LINK** · Modelis: **VIGI C340(2.8MM)** · EAN: **4897098688618** · Prekės kodas: **737617**


63,90 €

Kaina su PVM

 Be PVM: **52,81 €**

Sandėlyje


Prekė internetu

 Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ **4MP High Definition:** The camera comes with 4MP—more than enough pixels to pick up some of the more discrete details
- ✓ **24h Full-Color:** Obtain 24-hour color details, even in pitch-black conditions, via high-sensitivity sensor and included spotlight LEDs
- ✓ **Waterproof:** Reliable IP66 for stable outdoor performance
- ✓ **Smart Detection** (human detection, motion detection, area intrusion, line-crossing, video tampering): Receive notifications and check feeds when someone crosses a boundary, enters an area you've set, or obstructs the camera
- ✓ **H.265+:** Without using any extra bandwidth, your cameras transmit compressed crystal-clear video to save disk space, ease network loads, and reduce monitoring costs without sacrificing image quality
- ✓ **PoE/12V DC:** Two power supply ways not only give you more convenience but also make your wiring remarkably easy
- ✓ **VIGI App:** Manage your security from the palm of your hand with the VIGI app



Aprašymas

All The Colors,
All The Time

4MP Outdoor Full-Color Bullet Camera

Outdoor PoE Connection, Simple Wiring

Just connect your camera via an RJ45 cable, then power supply and data transmission are all settled. Waterproof hardware protect stable

performance in outdoor scenarios.

Clarity and Colors, All in One

Monitor 24-hour clear and colorful details even in pitch dark night. VIGI's Full-Color camera provides maximum 4MP resolutions and ensures colorful monitoring with its large-aperture lens, high-sensitivity sensor, and attached supplemental lights.

We keep an eye on your business.

Smart Detection

Receive notifications and check feeds when someone crosses a boundary, enters an area you've set, or obstructs the camera.

Motion Detection

Get instant notifications when your camera detects motion.

Area Intrusion

Set customized activity zones around key areas for more focused monitoring.

Line-Crossing

Set a boundary and receive an alert anytime a person crosses it from either or both directions.

Camera Tampering

Receive alerts when someone obstructs the camera.

Active Defense

Warn potential intruders instantly with sound and light when abnormal events

Every Event is Under Your Control.

VIGI camera intelligently detect activities, inform you instantly and response automatically by smart detection and two-way audio.

Never miss a detail.

SmartVid-Smart Video Enhancement

Smart IR

Keeps objects from being under-rendered when far away or overexposed when close to camera at night.

Wide Dynamic Range

Adjusts for lighting contrast to minimize shadowing effects and renders images true to life.

3D DNR

Removes abnormal pixelation to provide clearer video and eliminate distortion.

More compression. More savings. Same quality.

Without using any extra bandwidth, your cameras transmit compressed crystal-clear video to save disk space, ease network loads, and reduce monitoring costs without sacrificing image quality.

Flexible Management and Storage

Take full control over your security via four management methods: the web UI, NVR UI, VIGI app, and VIGI Security Manger. Local storage is available for each method, as well as on-board storage with SD card slot (up to 256 GB).

Discover the best way to power your camera.

PoE/12V DC

Two power supply ways not only give you more convenience but also make your wiring remarkably easy.

Flexible Installation

Find the perfect vantage point by simply securing your camera to ceiling, pole or wall.

One system. Full security.

Run your business with peace of mind.

The VIGI professional surveillance system by TP-Link is dedicated to protecting the business you've worked hard to build — whenever, wherever. Our outstanding functions, reliable quality guarantees, and simplified installation work together to ensure your business stays safe and sound.

Techninė specifikacija

Specifications	
Sandėlio grupė	> Netzwerk > Netzwerkkamera und Zubehör [+1996][-361]
Performance	
Type	IP security camera
Placement supported	Outdoor
Connectivity technology	Wired
Day/night mode	Yes
Design	
Mounting type	Ceiling/Wall/Pole
Product colour	Black, White
Form factor	Bullet
LED indicators	Yes
Housing material	Plastic
International Protection (IP) code	IP66
Camera	
Minimum illumination	0.005 lx
Lens viewing angle, horizontal	102°
Lens viewing angle, vertical	55°
Lens viewing angle, diagonal	122°
Tilt angle range	-90 - 90°
Pan range	-90 - 90°
Camera shutter speed	1/3 - 1/10000 s
Number of Privacy masking areas	4
Image sensor	
Sensor type	CMOS
Number of sensors	1
Optical sensor size	25.4 / 3 mm (1 / 3")

Progressive scan	Yes
Lens system	
Number of lenses	1
Detect distance	64 m
Observe distance	27 m
Recognize distance	13 m
Maximum aperture number	1.6
Identify distance	6 m
Fixed focal length	2.8 mm
Night vision	
Night vision	Yes
Night vision distance	30 m
LED type	IR
Number of illumination LEDs	2
Infra-red wavelength	850 nm
Video	
Maximum resolution	2560 x 1440 pixels
Total megapixels	4 MP
Video formats supported	H.264, H.264+, H.265, H.265+
Video compression formats	H.264, H.264+, H.265, H.265+
Supported graphics resolutions	1280 x 720 (HD 720), 1920 x 1080 (HD 1080), 2048 x 1280, 2304 x 1296, 2560 x 1440
Frame rate	30 fps
Image quality adjustment	Brightness, Contrast, Mirror, Saturation
Privacy masking	Yes
Bit rate control	Constant Bit Rate (CBR)/Variable Bit Rate (VBR)
Bit rate	256 Kbps - 4 Mbps
Back Light Compensation (BLC)	Yes
Highlight Compensation (HLC)	Yes
Digital Wide Dynamic Range (DWDR)	Yes
Region of Interest (ROI) encoding	Yes
Smart IR	Yes
3D positioning	Yes
Audio	
Built-in speaker(s)	Yes

Audio system	2-way
Audio input channels	1.0 channels
Audio output channels	1.0 channels
Sample rate	8 kHz
Signal-to-Noise Ratio (SNR)	52 dB
Built-in microphone	Yes
Bit rate range	0 - 64 Kbit/s
Network	
Ethernet LAN	Yes
Wi-Fi	No
Bluetooth	No
Ethernet interface type	Fast Ethernet
Networking standards	IEEE 802.3af, IEEE 802.3at
Supported network protocols	TCP/IP, UDP, ICMP, HTTP, HTTPS, DHCP, DNS, RTSP, NTP, UPnP UDP, SSL/TLS
Live view	Yes
Number of simultaneous live view channels	3 channels
Storage	
Built-in HDD	No
Card reader integrated	Yes
Compatible memory cards	MicroSD (TransFlash)
Maximum memory card size	256 GB
Ports & interfaces	
Ethernet LAN (RJ-45) ports	1
DC-in jack	Yes
Security	
Password protection	Yes
Video motion detection	Yes
IP address filtering	Yes
HTTPS encryption	Yes
Automatic Network Replenishment (ANR)	Yes
Network access storage (NAS)	Yes
Management features	
Web browser	Yes
Reset button	Yes

Power

Power source type	DC, PoE
Power consumption (typical)	3.4 W
Power consumption (max)	7 W
DC output voltage	12

Operational conditions

Operating temperature (T-T)	-30 - 60 °C
Storage temperature (T-T)	-40 - 60 °C
Operating relative humidity (H-H)	0 - 95%
Storage relative humidity (H-H)	0 - 95%

Weight & dimensions

Width	174 mm
Height	70 mm
Length	78 mm
Weight	280 g

Packaging data

Package width	128 mm
Package depth	218 mm
Package height	103 mm
Package weight	424 g
Package type	Box

Sustainability

Compliance certificates	BSMI, CE, KC
Sustainability compliance	Yes

Packaging content

Number of cameras	1
Mounting kit	Yes
Manual	Yes

Matmenys ir svoris

Matmenys (I × P × A)	23,00cm × 13,00cm × 10,00cm
Svoris	0,42kg