

Zyxel XMG1915-18EP Managed L2 2.5G Ethernet (100/1000/2500) Power over Ethernet (PoE)

Gamintojas: ZYXEL · Modelis: XMG1915-18EP-EU0101F · EAN: 4718937631490 · Prekės kodas: 737628



489,90 €

Kaina su PVM

Be PVM: 404,88 €

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Managed L2
- ✓ Quality of Service (QoS) support
- ✓ Basic switching RJ-45 Ethernet ports quantity: 16
- ✓ 10G support
- ✓ MAC address table: 16000 entries Switching capacity: 120 Gbit/s Multicast forwarding
- ✓ Rack mounting
- ✓ AC/PoE Power supply included Power over Ethernet (PoE)

Aprašymas

The Zyxel XMG1915 series is a versatile family of 2.5G Multi-Gig Smart Managed switches, available in three models with and without PoE connectivity. Each Ethernet port on these models supports 2.5G speed, and they are equipped with two 10G SFP+ ports to cater to your business's increasing need for high network speeds. The XMG1915 series is designed to support NebulaFlex, offering the most affordable Multi-Gig hybrid switch solution for the SB/SMB market. Whether you choose to set it up through the user-friendly Web GUI or the Nebula Control center for cloud-based unified management, configuration is a breeze. This series ensures that your network can keep up with the rapid growth in data demands without breaking the bank.

Techninė specifikacija

Specifications

Sandėlio grupė

> Netzwerk > Switches [+1607][-273]

Management features

Switch type

Managed

Switch layer	L2
Quality of Service (QoS) support	Yes
Ports & interfaces	
Basic switching RJ-45 Ethernet ports quantity	16
Basic switching RJ-45 Ethernet ports type	2.5G Ethernet (100/1000/2500)
Installed SFP modules quantity	0
Installed SFP+ modules quantity	0
SFP+ module slots quantity	2
Network	
Networking standards	IEEE 802.1p, IEEE 802.3ab, IEEE 802.3ae, IEEE 802.3at, IEEE 802.3az, IEEE 802.3bt, IEEE 802.3bz, IEEE 802.3x, IEEE 802.3z
10G support	Yes
VLAN support	Yes
Virtual LAN features	MAC address-based VLAN, Port-based VLAN, Voice VLAN
Data transmission	
MAC address table	16000 entries
Switching capacity	120 Gbit/s
Forwarding rate	89.2 Mpps
Jumbo frames support	Yes
Jumbo frames	12000
Packet buffer memory	1.5 MB
Security	
DHCP features	DHCP client, DHCP relay, DHCP snooping
IGMP snooping	Yes
Security algorithms	SNMP, SNMPv2, SNMPv3
MAC address filtering	Yes
SSH/SSL support	Yes
Authentication type	RADIUS
Multicast features	
Multicast support	Yes
Multicast features	Multicast forwarding
Design	
Rack mounting	Yes
LED indicators	Yes

Performance

Internal memory	256 MB
Flash memory	32 MB
Firmware upgradeable	Yes
Mean time between failures (MTBF)	954.032 h

Power

Power source	AC/PoE
Power supply included	Yes
AC input voltage	100 - 240 V
AC input frequency	50/60 Hz
Power consumption (max)	230.81 W

Power over Ethernet (PoE)

Power over Ethernet (PoE)	Yes
Power over Ethernet (PoE) ports quantity	8
Total Power over Ethernet (PoE) budget	180 W

Operational conditions

Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-40 - 70 °C
Operating relative humidity (H-H)	5 - 95%
Storage relative humidity (H-H)	5 - 95%

Weight & dimensions

Width	330 mm
Depth	230 mm
Height	44 mm
Weight	2.6 kg

Packaging content

Cables included	AC
-----------------	----

Matmenys ir svoris

Matmenys (I × P × A)	34,00cm × 40,00cm × 10,00cm
Svoris	3,64kg