

TP-Link VIGI C355 Bullet IP security camera Outdoor 2880 x 1620 pixels Wall

Gamintojas: **TP-LINK** · Modelis: **VIGI C355(6MM)** · EAN: **4895252506860** · Prekės kodas: **737715**



120,90 €

Kaina su PVM

Be PVM: **99,92 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 5MP Super-High Definition and 24h Full-Color
- ✓ People & Vehicle Analytics
- ✓ Human & Vehicle Classification
- ✓ Smart Detection
- ✓ Smart Video Enhancement Technology
- ✓ Active Defense and Two-Way Audio
- ✓ IP67 Waterproof
- ✓ H.265+ Compression Technology



Aprašymas

People & Vehicle Analytics

Search and filter to people or vehicle of interest based on many different attributes, making post-event search faster and easier.

Human & Vehicle Classification

Distinguish humans and vehicles from other objects and receive more accurate event notifications.

Smart Video Enhancement Technology

- True WDR: By analyzing and blending different exposures, True WDR ensures both bright and dark areas remain properly exposed, delivering a

well-balanced and natural-looking image even in environments with high-contrast lighting.△

- Smart IR: Smart IR dynamically adjusts infrared lighting to prevent overexposure and glare, improve visibility at different distances, and ensure clearer footage.
- 3D DNR: 3D DNR is a noise reduction technology that analyzes image data across frames to selectively reduce noise while preserving important details.
- White Balance: White Balance ensures that white appears neutral in an image, regardless of the lighting conditions.

Techninė specifikacija

Specifications	
Sandėlio grupė	> Netzwerk > Netzwerkkamera und Zubehör [+1996][-361]
Performance	
Type	IP security camera
Placement supported	Outdoor
Connectivity technology	Wired
Wide Dynamic Range (WDR)	Yes
Day/night mode	Yes
Infrared (IR) cut-off filter	Yes
Built-in light	Yes
Dynamic range	120 dB
Certification	CE, NTRA, VCCI, KC, BSMI, FCC, IC
Design	
Mounting type	Wall
Product colour	White
Form factor	Bullet
Housing material	Metal
International Protection (IP) code	IP67
Camera	
Minimum illumination	0.005 lx
Angle of rotation	360°
Lens viewing angle, horizontal	57.3°
Lens viewing angle, vertical	31.3°
Lens viewing angle, diagonal	67.2°
Tilt angle range	0 - 90°
Pan range	0 - 360°
Camera shutter speed	1/3 to 1/10000

Number of Privacy masking areas	4
Image sensor	
Sensor type	CMOS
Optical sensor size	25.4 / 2.7 mm (1 / 2.7")
Progressive scan	Yes
Lens system	
Number of lenses	1
Detect distance	120 m
Observe distance	50 m
Recognize distance	24 m
Maximum aperture number	1.6
Identify distance	12 m
Fixed focal length	6 mm
Night vision	
Night vision	Yes
Night vision distance	30 m
LED type	IR/White
Number of illumination LEDs	4
Infra-red wavelength	850 nm
Video	
Maximum resolution	2880 x 1620 pixels
Total megapixels	5 MP
Video compression formats	H.264, H.264+, H.265, H.265+
Supported graphics resolutions	1280 x 720 (HD 720), 1920 x 1080 (HD 1080), 2048 x 1280, 2304 x 1296, 2688 x 1520, 2880 x 1620
Frame rate	30 fps
Noise reduction	Yes
Noise reduction technology	3D noise reduction
Image quality adjustment	Brightness, Contrast, Mirror, Saturation, Sharpness
Privacy masking	Yes
Bit rate control	Constant Bit Rate (CBR), Constant Bit Rate (CBR)/Variable Bit Rate (VBR)
Bit rate	6 Mbps
Back Light Compensation (BLC)	Yes
Highlight Compensation (HLC)	Yes
Region of Interest (ROI) encoding	Yes

Smart IR	Yes
Audio	
Built-in speaker(s)	Yes
Audio system	2-way
Audio formats supported	G.711
Sample rate	8 kHz
Signal-to-Noise Ratio (SNR)	52 dB
Built-in microphone	Yes
Network	
Ethernet LAN	Yes
Wi-Fi	No
Bluetooth	No
Ethernet interface type	Fast Ethernet
Supported network protocols	TCP/IP, UDP, ICMP, HTTP, HTTPS, DHCP, DNS, RTSP, NTP, UPnP UDP, SSL/TLS
Storage	
Built-in HDD	No
Card reader integrated	Yes
Compatible memory cards	MicroSD (TransFlash)
Maximum memory card size	512 GB
Ports & interfaces	
Ethernet LAN (RJ-45) ports	1
DC-in jack	Yes
Security	
Password protection	Yes
IP address filtering	Yes
Privacy protection	Yes
Digest authentication	Yes
Management features	
Web browser	Yes
Power	
Power source type	DC, PoE
Power consumption (max)	10.7 W
DC output voltage	12
Operational conditions	

Operating temperature (T-T)	-30 - 60 °C
-----------------------------	-------------

Storage temperature (T-T)	-40 - 60 °C
---------------------------	-------------

Operating relative humidity (H-H)	0 - 95%
-----------------------------------	---------

Storage relative humidity (H-H)	0 - 95%
---------------------------------	---------

Weight & dimensions

Width	184 mm
-------	--------

Height	74 mm
--------	-------

Length	74 mm
--------	-------

Weight	525 g
--------	-------

Packaging content

Number of cameras	1
-------------------	---

Matmenys ir svoris

Svoris	0,76kg
--------	--------