

Lindy 4x2 HDMI 4K60 Matrix Zum Anschluss und Umschalten zwischen 4 HDMI-Quellen und 2 HDMI-Displays V2 Version (38084)

Gamintojas: **LINDY** · Modelis: **38084** · EAN: **4002888380843** · Prekės kodas: **738205**



159,90 €

Kaina su PVM

Be PVM: **132,15 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Switches between 4 HDMI source devices and 2 HDMI displays connected simultaneously
- ✓ Supports resolutions up to 4K 60Hz, with additional support for HDR
- ✓ Extract audio from HDMI to Toslink (Optical) and 3.5mm audio
- ✓ EDID Management system for controlling and ensuring the optimum resolution possible



Aprašymas

Switches between 4 HDMI source devices and 2 HDMI displays connected simultaneously
 Supports resolutions up to 4K 60Hz, with additional support for HDR
 Extract audio from HDMI to Toslink (Optical) and 3.5mm audio
 Supports ARC as well as a Downscaler-Function via HDMI Out B
 2 year warranty

Please note that two versions of this item exist with different connectors.

Please refer to the manuals to find out which version you have.

The Lindy 4x2 HDMI 4K60 Matrix Switch is a high performance solution for distributing content from multiple source devices to two displays.

Supporting HDMI 2.0 18G signals, this matrix allows for the transmission of clear 4K Ultra HD 60Hz resolutions, while additional support for High Dynamic Range ensures video content can be seen with enhanced brightness, greater contrasts and a much wider colour gamut, perfect for digital signage displays in retail or hospitality or creating engaging educational setups. HDCP 2.2 support ensures there are no issues with a variety of 4K content when connected to source devices including set top boxes, Blu-Ray players and 4K HDR media players.

As well as HDMI audio pass-through, a 3.5mm audio port allows for a separate connection of both analogue speaker systems, and optical audio devices such as soundbars and amplifiers, for creating immersive audio experiences to compliment the video on screen.

This matrix can be easily controlled via push button switching on the unit, while the included remote control also allows the user to have better control over multiple videos and displays, great for trade shows, training presentations or sales demonstrations.

Techninė specifikacija

Specifications	
Sandėlio grupė	> Netzwerk > Switches [+1607][-273]
Features	
Product type	AV matrix switcher
Maximum resolution	3840 x 2160 pixels
Bandwidth	18 Gbit/s
HDCP	Yes
HDCP version	2.2
Extended display identification data (EDID)	Yes
Design	
Housing colour	Black
Housing material	Metal
Display	
Built-in display	No
Ports & interfaces	
HDMI input ports quantity	4
HDMI output ports quantity	2
Digital audio optical out	1
USB ports quantity	1
Audio (L/R) out	1
DC-in jack	Yes
Power	
Output current	1000 mA
Output voltage	5 V

Operational conditions

Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-20 - 60 °C
Operating relative humidity (H-H)	20 - 90%

Logistics data

Harmonized System (HS) code	85299097
-----------------------------	----------

Weight & dimensions

Width	125 mm
Depth	95 mm
Height	25 mm
Weight	510 g
Package width	220 mm
Package depth	73 mm
Package height	154 mm
Package weight	636 g

Packaging content

Manual	Yes
Mounting brackets included	Yes
AC adapter included	Yes

Matmenys ir svoris

Svoris	0,72kg
--------	--------