

LevelOne KILBY 10-Port L2 Managed Gigabit PoE Switch, 2 x SFP, 802.3at/af PoE, 125W, 8 PoE Outputs

Gamintojas: **LEVELONE** · Modelis: **GEP-1061** · EAN: **4015867227350** · Prekės kodas: **738373**



313,90 €

Kaina su PVM

Be PVM: **259,42 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ With 8 *10/100/1000Mbps PoE ports and 2*1000Mbps SFP ports, with L2 network management
- ✓ Total 180W PoE power budget and usability, up to 2 ports at 90W(1-2 port), or 6 ports at 30W or 8 ports at 15.4W
- ✓ IEEE 802.3af/at/bt PoE compliant to simplify deployment and installation
- ✓ Support Web Smart configuration for PoE management, and QoS / VLAN / MSTP / Multi-broadcast / ports management features
- ✓ 6KV surge protection, 6KV contact / 8KV air ESD protection



Aprašymas

The GEP-1061 is LevelOne latest generation of 10-Port L2 Managed Gigabit PoE Switch, with 2 Gigabit SFP Uplink ports. also offers powerful Web Smart configuration for PoE management, and QoS / VLAN / MSTP / Multi-broadcast / ports management features. Switch that gives you a high-performance, low-cost, easy-to-use, seamless upgrade to boost your network to 1000Mbps. Increase the speed of your network backbone to a massive 20Gbps and bring Gigabit speeds all the way to your computers.

The GEP-1061 PoE-enabled switches features an IEEE 802.3af/at/bt standard, better PoE functionality with 180W PoE power budget and usability. supports up to 2 ports at 90W, or 6 ports at 30W or 8 ports at 15.4W to meet the increasing power demands of users. giving you flexibility in power allocation for a variety of powered devices enabling you to scale your operations to meet business growth, operational cost savings, and ease of

management.

Techninė specifikacija

Specifications	
Sandėlio grupė	> Netzwerk > Switches [+1607][-273]
Management features	
Switch type	Managed
Switch layer	L2
Quality of Service (QoS) support	Yes
Traffic classification	Yes
System event log	Yes
Ports & interfaces	
Basic switching RJ-45 Ethernet ports quantity	8
Basic switching RJ-45 Ethernet ports type	Gigabit Ethernet (10/100/1000)
Installed SFP modules quantity	0
Installed SFP+ modules quantity	0
Combo SFP ports quantity	2
Fiber ports quantity	2
Fiber optic connector	SFP
Console port	RJ-45
Network	
Networking standards	IEEE 802.1D, IEEE 802.1Q, IEEE 802.1p, IEEE 802.1s, IEEE 802.1w, IEEE 802.3, IEEE 802.3ab, IEEE 802.3ad, IEEE 802.3af, IEEE 802.3at, IEEE 802.3az, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z
10G support	No
Port mirroring	Yes
Flow control support	Yes
Link aggregation	Yes
Broadcast storm control	Yes
Rate limiting	Yes
Spanning tree protocol	Yes
Cable length detection	Yes
VLAN support	Yes
Virtual LAN features	MAC address-based VLAN, Port-based VLAN, Protocol-based VLAN, Tagged VLAN
Number of VLANs	4000

Optical fiber

Fiber ethernet cabling technology	100BASE-X, 1000BASE-X
-----------------------------------	-----------------------

Data transmission

MAC address table	8000 entries
-------------------	--------------

Switching capacity	20 Gbit/s
--------------------	-----------

Forwarding rate	14.9 Mpps
-----------------	-----------

Store-and-forward	Yes
-------------------	-----

Number of trunks	8
------------------	---

Number of queues	8
------------------	---

Static route	Yes
--------------	-----

Jumbo frames support	Yes
----------------------	-----

Jumbo frames	10000
--------------	-------

Packet buffer memory	4.1 MB
----------------------	--------

Security

DHCP features	DHCP client, DHCP snooping
---------------	----------------------------

Access Control List (ACL)	Yes
---------------------------	-----

Access Control List (ACL) rules	512
---------------------------------	-----

IGMP snooping	Yes
---------------	-----

MAC address filtering	Yes
-----------------------	-----

SSH/SSL support	Yes
-----------------	-----

BPDU filtering/protection	Yes
---------------------------	-----

Password protection	Yes
---------------------	-----

DoS attack prevention	Yes
-----------------------	-----

Multicast features

Multicast support	Yes
-------------------	-----

Protocols

IPv4 & IPv6 features	IPv6 Telnet, IPv6 ping, IPv6 tracert
----------------------	--------------------------------------

Design

Rack mounting	Yes
---------------	-----

Stackable	No
-----------	----

Product colour	Black
----------------	-------

Reset button	Yes
--------------	-----

LED indicators	Activity, Link, Power
----------------	-----------------------

Performance

Internal memory	32 MB
Noise level	0 dB
Telnet	Yes
Power	
Power source	AC
Power supply included	Yes
AC input voltage	100 - 240 V
AC input frequency	50 - 60 Hz
Power consumption (typical)	80 W
Power over Ethernet (PoE)	
Power over Ethernet (PoE)	Yes
Power over Ethernet (PoE) ports quantity	8
Power over Ethernet (PoE) power per port	30 W
Total Power over Ethernet (PoE) budget	125 W
Operational conditions	
Operating temperature (T-T)	-10 - 50 °C
Storage temperature (T-T)	-40 - 85 °C
Operating relative humidity (H-H)	10 - 95%
Weight & dimensions	
Width	181 mm
Depth	270 mm
Height	44 mm
Weight	800 g
Packaging content	
Cables included	AC, LAN (RJ-45)
Quick start guide	Yes
Rack mount kit	Yes
Packaging data	
Package type	Blister
Resource CD	Yes
Package width	255 mm
Package depth	82 mm
Package height	345 mm
Package weight	2 kg

Certificates	
Certification	CE class A, FCC, UL, VCCI, BSMI
Logistics data	
Country of origin	China
Harmonized System (HS) code	85176990
Matmenys ir svoris	
Svoris	2,05kg