

LevelOne 10-Port Fast Ethernet PoE Switch, 1 x Gigabit RJ45, 1 x Gigabit SFP, 8 PoE Outputs, 120W

Gamintojas: **LEVELONE** · Modelis: **FGP-1000** · EAN: **4015867187982** · Prekės kodas: **738816**



205,91 €

Kaina su PVM

Be PVM: **170,17 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Basic switching RJ-45 Ethernet ports quantity: 9
- ✓ 10BASE-T, 100BASE-TX, 1000BASE-T
- ✓ MAC address table: 4096 entries Switching capacity: 5.6 Gbit/s
- ✓ Power supply included Power over Ethernet (PoE)



Aprašymas

FGP-1000 is a 8-port 10/100Mbps Fast Ethernet Switch with Power over Ethernet (PoE) capability. With 8 dip switches, each PoE port can be manually set for On-Off control. FGP-1000 supports up to 30W on each LAN port when the DIP switch is in the ON position . Using a LevelOne PoE repeater, it is possible to extend the connection a further 100 meters, or even daisy-chain several PoE repeaters together for greater distances. Dual 10/100Mbps ports can connect with other edge switches or NVR as uplink ports.

- IEEE 802.3x Flow Control protects against lost packets for reliable data transmission
- 1000Mbps-Full-duplex, 10/100Mbps-Full/Half-duplex, Auto-Negotiation, Auto-MDI/MDIX
- PoE on/off control per port by dip switches
- Total PoE power budget: 120W, up to 30W per port
- Simple Plug and Play installation

Techninė specifikacija

Specifications	
Sandėlio grupė	> Netzwerk > Switches [+1607][-273]
Ports & interfaces	
Basic switching RJ-45 Ethernet ports quantity	9
Basic switching RJ-45 Ethernet ports type	Gigabit Ethernet (10/100/1000)
SFP module slots quantity	1
Fiber optic connector	SFP
Power connector	DC-in jack
Network	
Networking standards	IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3u, IEEE 802.3x
10G support	No
Copper ethernet cabling technology	10BASE-T, 100BASE-TX, 1000BASE-T
Full duplex	Yes
Auto MDI/MDI-X	Yes
Auto-negotiation	Yes
Optical fiber	
Fiber ethernet cabling technology	1000BASE-X
Fiber type	Single-mode
Data transmission	
MAC address table	4096 entries
Switching capacity	5.6 Gbit/s
Store-and-forward	Yes
Packet forwarding rate (1 Gbps)	1488000 pps
Packet forwarding rate (100 Mbps)	148000 pps
Packet forwarding rate (10 Mbps)	14880 pps
Design	
Rack mounting	No
Stackable	No
Product colour	Black, Grey
LED indicators	Activity, LAN, PoE, Power
On/off switch	Yes
Performance	
Buffer size	512 KB

Power

Power supply included	Yes
AC input voltage	100 - 240 V
AC input frequency	50 - 60 Hz
Output voltage	52 V
Power consumption (typical)	120 W
Power protection features	Over current, Short circuit

Power over Ethernet (PoE)

Power over Ethernet (PoE)	Yes
Power over Ethernet (PoE) ports quantity	9
Power over Ethernet (PoE) power per port	30 W
Total Power over Ethernet (PoE) budget	115 W

Operational conditions

Operating temperature (T-T)	0 - 45 °C
Storage temperature (T-T)	-40 - 70 °C
Operating relative humidity (H-H)	10 - 90%
Storage relative humidity (H-H)	10 - 90%

Weight & dimensions

Width	188 mm
Depth	118 mm
Height	38 mm
Weight	1.5 kg

Packaging content

Manual	Yes
--------	-----

Packaging data

AC adapter included	Yes
Package width	222 mm
Package depth	146 mm
Package height	78 mm
Package weight	1.7 kg

Certificates

Certification	FCC, CE, RoHS
---------------	---------------

Logistics data

Country of origin	Taiwan
-------------------	--------

Harmonized System (HS) code	85176990
-----------------------------	----------

Matmenys ir svoris

Svoris	1,81kg
--------	--------