

LevelOne 5-Port Gigabit Switch

Gamintojas: **LEVELONE** · Modelis: **GEU-0522** · EAN: **4015867202500** · Prekės kodas: **738918**



25,89 €

Kaina su PVM

Be PVM: **21,40 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 1000Mbps full-duplex, 10/100Mbps full/half-duplex, auto-negotiation, auto-MDI/MDIX
- ✓ Supports 4K MAC address auto-learning and auto-aging
- ✓ Quick and easy installation
- ✓ Minimize carbon footprint with advanced energy efficient technology (IEEE 802.3az)
- ✓ Package Contents



Aprašymas

The LevelOne GEU-0522 is a wire-speed, non-blocking networking device that provides 5 ports 10/100/1000Mbps Ethernet connections. All ports support auto-negotiation and auto-MDI/MDIX sensing, eliminating the need for crossover cables or Uplink Ports. Each port can be used as general network port or as connecting port into a router, server, hub or another network switch.

Techninė specifikacija

Specifications

Sandėlio grupė

> Netzwerk > Switches [+1607][-273]

Ports & interfaces

Basic switching RJ-45 Ethernet ports quantity	5
Basic switching RJ-45 Ethernet ports type	Gigabit Ethernet (10/100/1000)
Installed SFP modules quantity	0
Installed SFP+ modules quantity	0
Network	
Networking standards	IEEE 802.3, IEEE 802.3ab, IEEE 802.3az, IEEE 802.3u
10G support	No
Copper ethernet cabling technology	10BASE-T, 100BASE-T, 1000BASE-T
Full duplex	Yes
Auto MDI/MDI-X	Yes
Auto-negotiation	Yes
MAC address auto-learning supported	Yes
MAC address auto-aging supported	Yes
Data transmission	
MAC address table	1000 entries
Switching capacity	10 Gbit/s
Store-and-forward	Yes
Jumbo frames support	Yes
Jumbo frames	9000
Packet forwarding rate (1 Gbps)	1488100 pps
Packet forwarding rate (100 Mbps)	148810 pps
Packet forwarding rate (10 Mbps)	14880 pps
Design	
Stackable	No
Product colour	Black
LED indicators	Activity, Link, Power
Performance	
Buffer size	64 KB
Power	
Input current	0.6 A
Input voltage	5 V
Power over Ethernet (PoE)	
Power over Ethernet (PoE)	No
Operational conditions	

Operating temperature (T-T)	0 - 50 °C
Storage temperature (T-T)	-40 - 70 °C
Operating relative humidity (H-H)	10 - 90%
Storage relative humidity (H-H)	5 - 90%
Weight & dimensions	
Width	86 mm
Depth	23 mm
Height	89 mm
Weight	71.4 g
Packaging content	
Quick start guide	Yes
Packaging data	
AC adapter included	Yes
Package type	Box
Package width	95 mm
Package depth	82 mm
Package height	98 mm
Package weight	184 g
Certificates	
Certification	CE, FCC
Logistics data	
Country of origin	China
Master (outer) case width	495 mm
Master (outer) case length	191 mm
Master (outer) case height	516 mm
Harmonized System (HS) code	85176990
Master (outer) case gross weight	10.2 kg
Products per master (outer) case	50 pc(s)
Matmenys ir svoris	
Svoris	0,19kg