

LevelOne 34-Port Fast Ethernet PoE Switch, 802.3at/af PoE, 32 PoE Outputs, 2 x Gigabit RJ45, 250W

Gamintojas: **LEVELONE** · Modelis: **FGP-3400W250** · EAN: **4015867203248** · Prekės kodas: **738920**



857,90 €

Kaina su PVM

Be PVM: **709,01 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ PoE on/off control per port by dip switches
- ✓ IEEE 802.3af/at PoE PSE with 30W power budget
- ✓ IEEE 802.3af PoE compliant to simplify deployment and installation
- ✓ IEEE 802.3x Flow Control protects against lost packets for reliable data transmission
- ✓ 19-inch rackmount kit included



Aprašymas

The LevelOne FGP-3400 series are unmanaged PoE switches with 32 RJ45 PoE ports. The switches are IEEE 802.3af/at compliant, providing power and data over a single Ethernet cable to any PoE device, with a total power budget of 250/380/500/630/760W, or up to 30W per port. Ideal for desktops, they are also 19-inch rack-mountable, which provides convenient and flexible installation. The FGP-3400 switches are designed for small-to-medium businesses that require an affordable solution for deploying PoE infrastructure.

Techninė specifikacija

Specifications

Sandėlio grupė

> Netzwerk > Switches [+1607][-273]

Management features

Switch type	Unmanaged
-------------	-----------

Ports & interfaces

Basic switching RJ-45 Ethernet ports quantity	32
Basic switching RJ-45 Ethernet ports type	Fast Ethernet (10/100)
Installed SFP modules quantity	0
Installed SFP+ modules quantity	0
Fast Ethernet (copper) ports quantity	32
Gigabit Ethernet (copper) ports quantity	2

Network

Networking standards	IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3u, IEEE 802.3x
10G support	No
Copper ethernet cabling technology	10BASE-T, 100BASE-TX, 1000BASE-T
Cable types supported	Cat3, Cat4, Cat5, Cat5e, Cat6, Cat7
Full duplex	Yes
Flow control support	Yes

Data transmission

MAC address table	32000 entries
Switching capacity	10.4 Gbit/s
Jumbo frames support	Yes
Jumbo frames	16000
Packet forwarding rate (1 Gbps)	1488000 pps
Packet forwarding rate (100 Mbps)	148800 pps
Packet forwarding rate (10 Mbps)	14880 pps
Packet buffer memory	8 MB

Design

Rack mounting	Yes
Product colour	Black
LED indicators	LAN, PoE, Power, Uplink
On/off switch	Yes

Performance

Mean time between failures (MTBF)	74000 h
-----------------------------------	---------

Power

AC input voltage	100 - 240 V
------------------	-------------

AC input frequency	50 - 60 Hz
Power over Ethernet (PoE)	
Power over Ethernet (PoE)	Yes
Power over Ethernet plus (PoE+) ports quantity	32
Power over Ethernet (PoE) power per port	30 W
Total Power over Ethernet (PoE) budget	250 W
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-20 - 70 °C
Operating relative humidity (H-H)	10 - 90%
Storage relative humidity (H-H)	10 - 90%
Weight & dimensions	
Width	195 mm
Depth	480 mm
Height	45 mm
Weight	2.8 kg
Packaging content	
Cables included	AC
Quick start guide	Yes
Rack mount kit	Yes
Packaging data	
Package type	Box
Rubber feet	Yes
Package width	255 mm
Package depth	534 mm
Package height	95 mm
Package weight	3.3 kg
Logistics data	
Country of origin	Taiwan
Master (outer) case width	510 mm
Master (outer) case length	555 mm
Master (outer) case height	280 mm
Harmonized System (HS) code	85176990
Master (outer) case gross weight	17.8 kg

Products per master (outer) case	5 pc(s)
----------------------------------	---------

Matmenys ir svoris

Svoris	3,30kg
--------	--------