

Zyxel XS3800-28 Managed L2+ 10G Ethernet (100/1000/10000) Black

Gamintojas: ZYXEL · Modelis: XS3800-28-ZZ0101F · EAN: 4718937600960 · Prekės kodas: 738964



3 612,90 €

Kaina su PVM

Be PVM: 2 985,87 €

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Managed L2+ Web-based management
- ✓ Quality of Service (QoS) support Configuring Location Settings (CLI)
- ✓ Basic switching RJ-45 Ethernet ports quantity: 4
- ✓ 10G support 10GBASE-T, 100BASE-T, 1000BASE-T
- ✓ MAC address table: 32000 entries Switching capacity: 560 Gbit/s
- ✓ Access Control List (ACL)
- ✓ Rack mounting
- ✓ Power supply included



Aprašymas

Flexible port design

XS3800-28 offers a maximum of 24 10G fiber ports or 12 10G copper ports that are for most flexible adoption to your networks.

Essentials of a core switch

XS3800-28 is suitable for network aggregation such as SMB or campus networks that require low latency and high-density 10G backbone architectures with basic routing capability.

Restore Button

The "Restore" button saves the last workable configuration as the custom default, which allows you to fall back instantly in case of network

misconfigurations.

Dual Power

Two PSUs support active-standby power redundancy that triggers backup power supply if the main unit fails.

Designed for the long haul

Quality hardware design is how Zyxel differentiate ourselves from others. We ensure stability and longevity for XS3800-28 for your networks.

Techninė specifikacija

Specifications	
Sandėlio grupė	> Netzwerk > Switches [+1607][-273]
Management features	
Switch type	Managed
Switch layer	L2+
Quality of Service (QoS) support	Yes
Web-based management	Yes
Traffic classification	Yes
Traffic shaping	Yes
ARP inspection	Yes
Configuring Location Settings (CLI)	Yes
MIB support	Y
Ports & interfaces	
Basic switching RJ-45 Ethernet ports quantity	4
Basic switching RJ-45 Ethernet ports type	10G Ethernet (100/1000/10000)
Combo SFP ports quantity	8
SFP+ module slots quantity	16
Fiber optic connector	SFP+
Power connector	AC-in jack
Network	
Networking standards	IEEE 802.1D, IEEE 802.1ab, IEEE 802.1ad, IEEE 802.1p, IEEE 802.1s, IEEE 802.1w, IEEE 802.3ab, IEEE 802.3ae, IEEE 802.3ah, IEEE 802.3an, IEEE 802.3az, IEEE 802.3bz, IEEE 802.3x, IEEE 802.3z
10G support	Yes
Copper ethernet cabling technology	10GBASE-T, 100BASE-T, 1000BASE-T
Port mirroring	Yes
IP routing	Yes
Policy-based routing	Yes

Flow control support	Yes
Broadcast storm control	Yes
Rate limiting	Yes
Spanning tree protocol	Yes
Auto-negotiation	Yes
VLAN support	Yes
Optical fiber	
Fiber ethernet cabling technology	1000BASE-X
Data transmission	
MAC address table	32000 entries
Switching capacity	560 Gbit/s
Forwarding rate	416 Mpps
Packet buffer memory	4 MB
Security	
DHCP features	DHCP client, DHCP relay, DHCP server
Access Control List (ACL)	Yes
IGMP snooping	Yes
IGMP proxy	Yes
MAC address filtering	Yes
SSH/SSL support	Yes
Loop protection	Yes
BPDU filtering/protection	Yes
Authentication	MAC-based authentication
Password protection	Yes
Multicast features	
Multicast support	Yes
Design	
Rack mounting	Yes
Product colour	Black
Reset button	Yes
Performance	
Internal memory	8000 MB
Flash memory	64 MB
Mean time between failures (MTBF)	656274.78 h

Power

Power supply included	Yes
Redundant power supply (RPS) support	Yes
Number of power supply units	2
AC input voltage	100 - 240 V
AC input frequency	50 - 60 Hz

Power over Ethernet (PoE)

Power over Ethernet (PoE)	No
---------------------------	----

Operational conditions

Operating temperature (T-T)	0 - 50 °C
Storage temperature (T-T)	-40 - 70 °C
Operating relative humidity (H-H)	10 - 95%
Storage relative humidity (H-H)	10 - 95%

Weight & dimensions

Width	441 mm
Depth	340 mm
Height	44 mm
Weight	4.81 kg

Packaging content

Cables included	AC
Rack mount kit	Yes

Logistics data

Harmonized System (HS) code	85176990
-----------------------------	----------

Matmenys ir svoris

Svoris	7,18kg
--------	--------