

LevelOne 50-Port Fast Ethernet Switch, 2 x Gigabit SFP/RJ45 Combo

Gamintojas: **LEVELONE** · Modelis: **FGU-5021** · EAN: **4015867198407** · Prekės kodas: **739560**



243,90 €

Kaina su PVM

Be PVM: **201,57 €**

Sandėlyje




Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Basic switching RJ-45 Ethernet ports quantity: 50 Console port: RJ-45
- ✓ 10BASE-T, 100BASE-T, 1000BASE-T, 1000BASE-TX
- ✓ MAC address table: 8000 entries Switching capacity: 13.6 Gbit/s
- ✓ Rack mounting
- ✓ Power supply included



Aprašymas

- 10/100Mbps, full/half-duplex, auto-negotiation, auto-MDI/MDIX
- 9K jumbo frames to increase data transfer rates
- Supports 8K MAC address auto-learning and auto-aging
- 19-inch metal housing
- Quick and easy installation

Fast connections and fiber distances

FGU-5021 is a 48-port Fast Ethernet Switch (10/100 Mbps) that gives you a high-performance, low-cost, easy-to-use, solution to expand your network reach. With 2 Gigabit ports and 2 SFP Port , you're able to connect to other networks for flexible and powerful deployment options.

Plug and Play, Flexible and Easy

GSW-5150 is plug-and-play so no configuration is required. Providing auto MDI/MDI-X cable detection on all ports eliminates the need for crossover cables or Uplink ports. Each port can be used as general ports or Uplink ports, and any port can be simply plugged into a server, a hub, a router or a switch, using a straight cable or crossover cable. Diagnostic LEDs which display link status and activity, allowing you to quickly detect and correct problems on the network.

Techninė specifikacija

Specifications	
Sandėlio grupė	> Netzwerk > Switches [+1607][-273]
Ports & interfaces	
Basic switching RJ-45 Ethernet ports quantity	50
Basic switching RJ-45 Ethernet ports type	Fast Ethernet (10/100)
Fast Ethernet (copper) ports quantity	48
Gigabit Ethernet (copper) ports quantity	2
Combo SFP ports quantity	2
Fiber optic connector	SFP
Console port	RJ-45
Network	
Networking standards	IEEE 802.3, IEEE 802.3az, IEEE 802.3u
10G support	No
Copper ethernet cabling technology	10BASE-T, 100BASE-T, 1000BASE-T, 1000BASE-TX
Full duplex	Yes
Auto MDI/MDI-X	Yes
Auto-negotiation	Yes
MAC address auto-learning supported	Yes
MAC address auto-aging supported	Yes
Optical fiber	
Fiber ethernet cabling technology	100BASE-X, 1000BASE-X
Data transmission	
MAC address table	8000 entries
Switching capacity	13.6 Gbit/s
Store-and-forward	Yes
Jumbo frames support	Yes
Jumbo frames	9000
Packet buffer memory	4 MB
Design	

Rack mounting	Yes
Product colour	Grey
Housing material	Metal
LED indicators	Activity, Link, Power
Performance	
Internal memory	16 MB
Power	
Power supply included	Yes
AC input voltage	100 - 240 V
AC input frequency	50 - 60 Hz
Power consumption (typical)	28.6 W
Power over Ethernet (PoE)	
Power over Ethernet (PoE)	No
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-40 - 70 °C
Operating relative humidity (H-H)	10 - 90%
Storage relative humidity (H-H)	5 - 90%
Weight & dimensions	
Width	44 mm
Depth	230 mm
Height	440 mm
Weight	2.7 kg
Packaging content	
Cables included	AC
Quick start guide	Yes
Packaging data	
Package type	Gift box
Package width	375 mm
Package depth	100 mm
Package height	510 mm
Package weight	2.82 kg
Certificates	
Certification	CE/FCC

Logistics data

Country of origin	China
Master (outer) case width	520 mm
Master (outer) case length	395 mm
Master (outer) case height	535 mm
Harmonized System (HS) code	85176990
Master (outer) case gross weight	13.8 kg
Products per master (outer) case	5 pc(s)

Matmenys ir svoris

Svoris	3,23kg
--------	--------