

Lindy 7.5m DisplayPort 1.2 Cable, Anthra Line

Gamintojas: **LINDY** · Modelis: **36485** · EAN: **4002888364850** · Prekės kodas: **739675**



44,90 €

Kaina su PVM

Be PVM: **37,11 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Professional choice DisplayPort 1.2 cable for commercial and high performance AV and IT installations
- ✓ Supports UHD resolutions up to 4096x2160@60Hz 4:4:4 10bit
- ✓ Robust PVC housing, gold plated connectors and contacts
- ✓ Triple shielded cable, corrosion resistant tinned copper 26AWG conductors
- ✓ DisplayPort 1.2 compliant: 3D, 4K, 21.6Gbps; 10 year warranty



Aprašymas

From the Lines cable connectivity concept developed by Lindy, Anthra Line DisplayPort cables are the professional choice for high performance connections in commercial AV and IT installations.

Anthra Line DisplayPort cables are premium connections that feature triple shielded with 26AWG tinned copper conductors for performance and corrosion resistance. High quality gold plated contacts and connectors maintain optimal signal integrity and maximum reliability.

UHD resolutions up to 4K 4096x2160@60Hz 4:4:4 10bit, including stereoscopic 3D and HDCP are supported. DisplayPort 1.2 technology ensures compatibility with all DisplayPort enabled devices.

Anthra Line DisplayPort cables are available in lengths: 0.5m, 1m, 2m, 3m, 5m, 7.5m and 10m.

Techninė specifikacija

Specifications	
Sandėlio grupė	> Kabel und Adapter > Displayport Kabel und Adapter [+1987][-131]
Features	
Cable length	7.5 m
Connector 1	DisplayPort
Connector 2	DisplayPort
Connector 1 gender	Male
Connector 2 gender	Male
Maximum resolution	4096 x 2160 pixels
Product colour	Black
Connector contacts plating	Gold
DisplayPort version	1.2
Supported graphics resolutions	4096 x 2160
Supported video modes	2160p
Maximum refresh rate	60 Hz
Cable material	Copper
Jacket material	Polyvinyl chloride (PVC)
AWG wire size	26
Data transfer rate	21.6 Gbit/s
Operational conditions	
Operating temperature (T-T)	-10 - 80 °C
Storage temperature (T-T)	-25 - 85 °C
Certificates	
Compliance certificates	RoHS
Certification	REACH, UL
Weight & dimensions	
Cable diameter	7.5 mm
Packaging data	
Package type	Polybag
Logistics data	
Harmonized System (HS) code	84733080
Matmenys ir svoris	

Svoris

0,61kg