

TP-Link IES206GPP network switch Managed Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) Black

Gamintojas: **TP-LINK** · Modelis: **IES206GPP** · EAN: **1210002602051** · Prekės kodas: **740025**



271,90 €

Kaina su PVM

Be PVM: **224,71 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 4× Gigabit RJ45 Ports (1× PoE++, 3× PoE+)
- ✓ 1× Gigabit Combo RJ45/SFP Slot, 1× Gigabit SFP Slot
- ✓ 120W Power Budget* with up to 60W for PoE++ Port
- ✓ Professional Industrial-Grade Design: -40~75°C Operating Temperature, 6kV Lighting Protection, and 1+1 Redundant Power Input
- ✓ Abundant Features: Up to 820ft (250m) PoE,** VLAN, QoS, and STP/RSTP
- ✓ Centralized Cloud Management via the Web or Omada App
- ✓ Durable IP40 Aluminum Casing and DIN-rail / Wall-mount Design



Aprašymas

Industrial-Grade Protection Built for Harsh Environments

Enhanced Networking Stability and Security

Easy Operation and Maintenance with Omada's Free Cloud Management

Techninė specifikacija

Specifications	
Sandėlio grupė	> Netzwerk > Switches [+1607][-273]
Management features	
Switch type	Managed
Ports & interfaces	
Basic switching RJ-45 Ethernet ports quantity	4
Basic switching RJ-45 Ethernet ports type	Gigabit Ethernet (10/100/1000)
Combo SFP ports quantity	1
SFP module slots quantity	1
Network	
Networking standards	IEEE 802.1D, IEEE 802.1Q, IEEE 802.1p, IEEE 802.1w, IEEE 802.3af, IEEE 802.3at, IEEE 802.3bt, IEEE 802.3x
10G support	No
Port mirroring	Yes
Flow control support	Yes
Link aggregation	Yes
Broadcast storm control	Yes
Auto MDI/MDI-X	Yes
Spanning tree protocol	Yes
Ethernet LAN data rates	10,100,1000 Mbit/s
Auto-negotiation	Yes
Data transmission	
MAC address table	8000 entries
Switching capacity	12 Gbit/s
Forwarding rate	8.93 Mpps
Store-and-forward	Yes
Jumbo frames support	Yes
Jumbo frames	15000
Security	
DHCP features	DHCP client
IGMP snooping	Yes
Multicast features	
Multicast support	Yes

Design

Rack mounting	Yes
Product colour	Black
Wall mountable	Yes
DIN rail mounting	Yes

Performance

Fanless	Yes
---------	-----

Power

Power source	DC/PoE
Redundant power supply (RPS) support	Yes
DC input voltage	12 - 57 V

Power over Ethernet (PoE)

Power over Ethernet (PoE)	Yes
Power over Ethernet (PoE) type supported	PoE+, PoE++ (4PPoE)
Power over Ethernet plus (PoE+) ports quantity	3
Power over Ethernet 4PPoE (PoE++) ports quantity	1
Power over Ethernet (PoE) power per port	30 W
Total Power over Ethernet (PoE) budget	120 W

Operational conditions

Operating temperature (T-T)	-40 - 75 °C
Storage temperature (T-T)	-40 - 85 °C
Operating relative humidity (H-H)	5 - 95%
Storage relative humidity (H-H)	5 - 95%

Weight & dimensions

Width	155 mm
Depth	120 mm
Height	60 mm

Packaging content

Quick start guide	Yes
-------------------	-----

Certificates

Certification	FCC, CE, RoHS
---------------	---------------

Matmenys ir svoris

Matmenys (I × P × A)	19,00cm × 20,00cm × 10,00cm
Svoris	1,37kg