

ASUS QG-U1080 Unmanaged 2.5G Ethernet (100/1000/2500) White

Gamintojas: **ASUS** · Modelis: **90IG0A00-M03B00** · EAN: **4711387868720** · Prekės kodas: **740070**



113,90 €

Kaina su PVM

Be PVM: 94,13 €

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Upgraded 2.5G ports and 10G SFP+ - Seamlessly upgrade to 2.5G by using standard CAT5e Ethernet cables to enjoy faster network performance.
- ✓ Support four intelligent functions - priority, EEE, port isolation, and static trunk. One switch is all you need to safeguard and optimize your home or business network.
- ✓ Plug and Play, Effortless Setup - Setting up your network has never been easier! Simply connect your devices, and you're good to go—no complicated configurations required.
- ✓ Versatile Networking Expansion - You can connect 2.5G/10G-compatible devices, including NAS , AP, Gaming PCs, and 4K streaming devices to achieve a more comprehensive network setup.



Aprašymas

Upgrade to the 2.5G Ultra-Fast Network

Experience lightning speed and seamless connectivity like never before.

Genuine WiFi Integration for Real Performance

The QG-U1080 unlocks the full potential of WiFi 6/7 APs. Unlike traditional Gigabit Ethernet switches, it removes performance limitations, delivering a superior and uninterrupted experience.

Techninė specifikacija

Specifications	
Sandėlio grupė	> Netzwerk > Switches [+1607][-273]
Management features	
Switch type	Unmanaged
Ports & interfaces	
Basic switching RJ-45 Ethernet ports quantity	8
Basic switching RJ-45 Ethernet ports type	2.5G Ethernet (100/1000/2500)
Fiber ports quantity	2
Fiber optic connector	SFP+
Network	
Networking standards	IEEE 802.3ab, IEEE 802.3bz, IEEE 802.3u, IEEE 802.3x, IEEE 802.3az
10G support	Yes
Copper ethernet cabling technology	100BASE-TX, 1000BASE-T, 2500BASE-T
Cable types supported	Cat5e
Flow control support	Yes
Data transmission	
MAC address table	16000 entries
Forwarding rate	59.52 Mpps
Jumbo frames support	Yes
Jumbo frames	10000
Packet buffer memory	8 MB
Design	
Product colour	White
LED indicators	Power, Link
Power	
Power source	DC
DC input voltage	12 V
Power over Ethernet (PoE)	
Power over Ethernet (PoE)	No
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-40 - 70 °C

Operating relative humidity (H-H)	10 - 90%
-----------------------------------	----------

Storage relative humidity (H-H)	5 - 90%
---------------------------------	---------

Weight & dimensions

Width	193 mm
-------	--------

Depth	84.1 mm
-------	---------

Height	26 mm
--------	-------

Weight	420 g
--------	-------

Packaging content

Quick start guide	Yes
-------------------	-----

Packaging data

Package type	Box
--------------	-----

Package width	210 mm
---------------	--------

Package depth	106 mm
---------------	--------

Package height	84 mm
----------------	-------

Package weight	678 g
----------------	-------

Matmenys ir svoris

Matmenys (l × p × A)	8,00cm × 19,00cm × 3,00cm
----------------------	---------------------------

Svoris	0,65kg
--------	--------