

TP-Link Omada 10-Port Gigabit Smart Switch with 8-Port PoE+

Gamintojas: **TP-LINK** · Modelis: **SG2210P** · EAN: **6935364030698** · Prekės kodas: **740331**



136,90 €

Kaina su PVM

Be PVM: **113,14 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 8x Gigabit 802.3af/at PoE+ ports and 2x Gigabit SFP slots
- ✓ 61 W total PoE budget with up to 30 W PoE output per port*
- ✓ Centralized cloud management via the web or the Omada app†
- ✓ Standalone management via web, CLI, SNMP, and RMON
- ✓ Static Routing helps route internal traffic for higher efficiency
- ✓ VLAN, ACL, QoS, and IGMP Snooping
- ✓ Fanless design for silent operation
- ✓ Durable metal casing and desktop/wall mounting design



Aprašymas

TP-Link's brand new Omada smart switches provide huge upgrade comparing with previous versions. The switches can be managed by Omada SDN Controller, which provides professional and reliable one-step solutions. Integrated L2 and L2+ features such as 802.1Q VLAN, QoS, IGMP Snooping and static routing provide cost-effective networking solutions for small and medium-sized businesses without sacrificing enhanced usability and strong performance.

Techninė specifikacija

Specifications

Sandėlio grupė

> Netzwerk > Switches [+1607][-273]

Management features

Switch type	Managed
Switch layer	L2/L2+
Quality of Service (QoS) support	Yes
Web-based management	Yes
Cloud-managed	Yes
ARP inspection	Yes
Configuring Location Settings (CLI)	Yes
System event log	Yes

Ports & interfaces

Basic switching RJ-45 Ethernet ports quantity	8
Basic switching RJ-45 Ethernet ports type	Gigabit Ethernet (10/100/1000)
Installed SFP modules quantity	0
Installed SFP+ modules quantity	0
SFP module slots quantity	2
Power connector	DC-in jack

Network

Networking standards	IEEE 802.1D, IEEE 802.1Q, IEEE 802.1p, IEEE 802.1s, IEEE 802.1w, IEEE 802.1x, IEEE 802.3, IEEE 802.3ab, IEEE 802.3ad, IEEE 802.3af, IEEE 802.3i, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z
10G support	No
Port mirroring	Yes
Flow control support	Yes
Link aggregation	Yes
Broadcast storm control	Yes
Rate limiting	Yes
Auto MDI/MDI-X	Yes
Spanning tree protocol	Yes
Auto-negotiation	Yes
VLAN support	Yes

Data transmission

MAC address table	8000 entries
Switching capacity	20 Gbit/s
Forwarding rate	14.88 Mpps
Jumbo frames support	Yes

Jumbo frames	9000
Packet buffer memory	4.1 MB
Security	
Access Control List (ACL)	Yes
IGMP snooping	Yes
Static port security	Yes
SSH/SSL support	Yes
BPDU filtering/protection	Yes
IP-MAC-Port binding	Yes
Authentication	MAC-based authentication, Port-based authentication
Multicast features	
Multicast support	Yes
Multicast Listener Discovery (MLD) snooping	Y
Protocols	
IPv4 & IPv6 features	Dual stack IPv4/IPv6
Design	
Product colour	Black
LED indicators	Yes
Performance	
Firmware upgradeable	Yes
Power	
Power source	DC/PoE
Power supply included	Yes
AC input voltage	100 - 240 V
AC input frequency	50/60 Hz
Power consumption (max)	77.8 W
Power over Ethernet (PoE)	
Power over Ethernet (PoE)	Yes
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-40 - 70 °C
Operating relative humidity (H-H)	10 - 90%
Storage relative humidity (H-H)	5 - 90%
Weight & dimensions	

Width	209 mm
Depth	126 mm
Height	26 mm
Packaging content	
Cables included	AC
Manual	Yes
Certificates	
Certification	CE, FCC, RoHS
Matmenys ir svoris	
Matmenys (l × P × A)	13,00cm × 21,00cm × 3,00cm
Svoris	1,31kg