

Zyxel XGS2210-52 Managed L2 Gigabit Ethernet (10/100/1000) 1U Black

Gamintojas: **ZYXEL** · Modelis: **XGS2210-52-EU0101F** · EAN: **4718937587902** · Prekės kodas: **740382**



772,90 €

Kaina su PVM

Be PVM: **638,76 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Managed L2 Web-based management
- ✓ Quality of Service (QoS) support
- ✓ Basic switching RJ-45 Ethernet ports quantity: 48
- ✓ 10G support
- ✓ MAC address table: 16000 entries Switching capacity: 176 Gbit/s
- ✓ Access Control List (ACL)
- ✓ 1U Rack mounting Stackable



Aprašymas

Agile traffic control for converged networking applications

ZyXEL XGS2210/GS2210 Series has a rich Layer 2 feature set that can shape the traffic for diverse VoIP, video conference, IPTV and IP surveillance deployments and provide hotels, businesses and educational institutions greater agility and more effective traffic management for the converged applications of today.

ZyXEL One Network experience

Aiming for relieving our customers from repetitive operations of deploying and managing a network, ZyXEL One Network is designed to simplify the

configuration, management, and troubleshooting, allowing our customers to focus on the business priorities. ZyXEL One Network presents an easy-to-use tool, ZyXEL One Network Utility (ZON Utility), to realize speed network setup. ZyXEL Smart Connect allows ZyXEL networking equipment to be aware and recognize each other and further facilitating the network maintenance via one-click remote functions such as factory reset or power cycling. ZyXEL One Network redefines the network integration across multiple networking products from switch to Wi-Fi AP and to Gateway.

High-powered Power over Ethernet (PoE)

The ZyXEL XGS2210/GS2210 Series PoE switches support the IEEE 802.3af PoE and 802.3at PoE Plus standards, which provide up to 30 watts of power per port for advanced Powered Devices (PD) like 802.11ac wireless APs and video IP phones. The high power budget enables the XGS2210/GS2210 PoE switches to comfortably accommodate the PDs required in a modern network edge.

High-powered Power over Ethernet (PoE)

The ZyXEL XGS2210/GS2210 Series PoE switches support the IEEE 802.3af PoE and 802.3at PoE Plus standards, which provide up to 30 watts of power per port for advanced Powered Devices (PD) like 802.11ac wireless APs and video IP phones. The high power budget enables the XGS2210/GS2210 PoE switches to comfortably accommodate the PDs required in a modern network edge.

Techninė specifikacija

Specifications	
Sandėlio grupė	> Netzwerk > Switches [+1607][-273]
Management features	
Switch type	Managed
Switch layer	L2
Quality of Service (QoS) support	Yes
Web-based management	Yes
Traffic shaping	Yes
ARP inspection	Yes
System event log	Yes
MIB support	RFC 1066, RFC 1213, RFC 1493, RFC 1643, RFC 1757, RFC 2011, RFC 2233, RFC 2358, RFC 2674, RFC 2819, RFC 2925, RFC 3621, RFC 4022, RFC 4113, RFC 4292, RFC 4293
Ports & interfaces	
Basic switching RJ-45 Ethernet ports quantity	48
Basic switching RJ-45 Ethernet ports type	Gigabit Ethernet (10/100/1000)
Installed SFP modules quantity	0
Installed SFP+ modules quantity	0
SFP+ module slots quantity	4
Network	
Networking standards	IEEE 802.1D, IEEE 802.1Q, IEEE 802.1ab, IEEE 802.1p, IEEE 802.1s, IEEE 802.1w, IEEE 802.1x, IEEE 802.3, IEEE 802.3ab, IEEE 802.3ad, IEEE 802.3af, IEEE 802.3at, IEEE 802.3az, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z

10G support	Yes
Port mirroring	Yes
IP routing	Yes
Flow control support	Yes
Link aggregation	Yes
Broadcast storm control	Yes
Rate limiting	Yes
Spanning tree protocol	Yes
MAC address auto-learning supported	Yes
VLAN support	Yes
Virtual LAN features	Private VLAN, Protocol-based VLAN, Port-based VLAN
Data transmission	
MAC address table	16000 entries
Switching capacity	176 Gbit/s
Throughput	130.9 Mpps
Number of queues	8
Jumbo frames support	Yes
Jumbo frames	9000
Packet buffer memory	1.5 MB
Security	
DHCP features	DHCP client
Access Control List (ACL)	Yes
IGMP snooping	Yes
Security algorithms	802.1x RADIUS, SNMP, SSH, SSH-2
MAC address filtering	Yes
SSH/SSL support	Yes
BPDU filtering/protection	Yes
Authentication	MAC-based authentication
Multicast features	
Multicast support	Yes
Design	
Rack mounting	Yes
Stackable	Yes
Form factor	1U

Product colour	Black
Safety	LVD, BSMI
Electromagnetic compatibility	FCC 15 (A), CE (A), BSMI
Performance	
Noise level	44.15 dB
Plug and Play	Yes
Mean time between failures (MTBF)	970594 h
Power	
AC input voltage	100 - 240 V
AC input frequency	50 - 60 Hz
Power consumption (max)	45 W
Power over Ethernet (PoE)	
Power over Ethernet (PoE)	No
Operational conditions	
Operating temperature (T-T)	0 - 50 °C
Storage temperature (T-T)	-40 - 70 °C
Operating relative humidity (H-H)	10 - 95%
Storage relative humidity (H-H)	10 - 90%
Heat dissipation	153.3 BTU/h
Weight & dimensions	
Width	441 mm
Depth	270 mm
Height	45 mm
Weight	3.86 kg
Packaging content	
Cables included	AC
Rack mount kit	Yes
Packaging data	
Package width	622 mm
Package depth	358 mm
Package height	108 mm
Package weight	4.92 kg
Certificates	
Certification	RoHS

Logistics data

Harmonized System (HS) code	85176990
-----------------------------	----------

Matmenys ir svoris

Matmenys (l × p × A)	33,00cm × 44,00cm × 5,00cm
----------------------	----------------------------

Svoris	5,04kg
--------	--------